

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 1 00028 T0000 epple 28 T / thixotropic
Print date 26.04.2023 Revision date 06.04.2023
Version 8.0 26.04.2023

EN
Page 1 / 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier): 1 00028 T0000
Trade name/designation epple 28 T / thixotropic
Sealant
UFI: VWD0-309N-800N-27HC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Sealing material for the sealing of different parts / buildinggroups

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

E. Epple & Co. GmbH
Hertzstr. 8
71083 Herrenberg

Telephone: +49 7032 / 9771-17
Telefax: +49 7032 / 9771-60
www.epple-chemie.de

Department responsible for information:

laboratory

E-mail (competent person)

labor@epple-chemie.de

1.4. Emergency telephone number

Information center against poisoning Bonn

+49 (0) 228 / 19 240 (Advice in German)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Carc. 2 / H351	Carcinogenicity	Suspected of causing cancer.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapour.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P501 Dispose of contents / container to a certified waste management company.

Hazard components for labelling

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]
4-methylpentan-2-one
quartz

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 1 00028 T0000 epple 28 T / thixotropic
Print date 26.04.2023 Revision date 06.04.2023
Version 8.0 26.04.2023

EN
Page 2 / 10

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. **Other hazards**

No information available.

SECTION 3: Composition/information on ingredients

3.2. **Mixtures** *

Description solution of various copolymers, filled

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification: // Remark	weight-%
203-550-1 108-10-1 606-004-00-4	01-2119473980-30 4-methylpentan-2-one Flam. Liq. 2 H225 / Carc. 2 H351 / Acute Tox. 4 H332 / STOT SE 3 H336 / Eye Irrit. 2 H319 / EUH066 Acute toxicity estimate (ATE): ATE (inhalation, vapour): 11,00 mg/L	24,9 - 49,9
201-159-0 78-93-3 606-002-00-3 238-878-4 14808-60-7	01-2119457290-43 butanone Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336 / EUH066 quartz STOT RE 1 H372	9,9 - 19,9 0,9 - 2,4
25036-25-3	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[[1-methylethylidene]bis(4,1-phenyleneoxymethylene)]bis[oxirane] Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317	0,9 - 2,4

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. **Description of first aid measures**

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. **Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. **Extinguishing media**

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 1 00028 T0000 epple 28 T / thixotropic
Print date 26.04.2023 Revision date 06.04.2023
Version 8.0 26.04.2023

EN
Page 3 / 10

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Floors must be electrically conductive.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

4-methylpentan-2-one

*

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 1 00028 T0000 epple 28 T / thixotropic
Print date 26.04.2023 Revision date 06.04.2023
Version 8.0 26.04.2023

EN
Page 4 / 10

Index No. 606-004-00-4 / EC No. 203-550-1 / CAS No. 108-10-1

TWA: 208 mg/m³; 50 ppm
STEL: 416 mg/m³; 100 ppm

butanone

Index No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

TWA: 600 mg/m³; 200 ppm
STEL: 899 mg/m³; 300 ppm

Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

butanone

Index No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

DNEL long-term dermal (systemic), Workers: 1161 mg/kg
DNEL long-term inhalative (systemic), Workers: 600 mg/m³
DNEL long-term oral (repeated), Consumer: 31 mg/kg
DNEL acute dermal, short-term (local), Consumer: 412 mg/kg
DNEL long-term inhalative (systemic), Consumer: 106 mg/m³

4-methylpentan-2-one

Index No. 606-004-00-4 / EC No. 203-550-1 / CAS No. 108-10-1

DNEL long-term dermal (systemic), Workers: 11,8 mg/kg bw/day
DNEL acute inhalative (local), Workers: 208 mg/m³
DNEL long-term inhalative (local), Workers: 83 mg/m³

PNEC:

butanone

Index No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

PNEC aquatic, freshwater: 55,8 mg/L
PNEC aquatic, marine water: 55,8 mg/L
PNEC aquatic, intermittent release: 55,8 mg/L
PNEC sediment, freshwater: 284,7 mg/kg
PNEC sediment, marine water: 284,7 mg/kg
PNEC, soil: 22,5 mg/kg

4-methylpentan-2-one

Index No. 606-004-00-4 / EC No. 203-550-1 / CAS No. 108-10-1

PNEC aquatic, freshwater: 0,6 mg/L
PNEC aquatic, marine water: 0,06 mg/L
PNEC aquatic, intermittent release: 1,5 mg/L
PNEC sediment, freshwater: 8,27 mg/kg
PNEC sediment, marine water: 0,83 mg/kg
PNEC, soil: 1,3 mg/kg

8.2. **Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Use combination filters according to EN 14387.

Suitable respiratory protection apparatus: ABEK-P2

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Article No.: 1 00028 T0000 epple 28 T / thixotropic
Print date 26.04.2023 Revision date 06.04.2023
Version 8.0 26.04.2023

EN
Page 5 / 10

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear eye glasses with side protection according to EN 166.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties *

Physical state:	Liquid
Appearance:	Paste
Colour:	blue
Odour:	Ketone
Odour threshold:	not applicable
Melting point/freezing point:	-86 °C Source: butanone
Initial boiling point and boiling range:	80 °C Source: butanone
Flammability:	Highly flammable liquid and vapour.
Lower and upper explosion limit:	
Lower explosion limit:	1,2 Vol-% Source: 4-methylpentan-2-one
Upper explosion limit:	11,5 Vol-% Source: butanone
Flash point:	-4 °C
Auto-ignition temperature:	448 °C Source: 4-methylpentan-2-one
Decomposition temperature:	not applicable
pH at 20 °C:	not relevant
Cinematic viscosity (40°C):	90000 mm²/s
Viscosity at 20 °C:	80 - 120 Pa*s
Solubility(ies):	
Water solubility at 20 °C:	insoluble
Partition coefficient: n-octanol/water:	see section 12
Vapour pressure at 20 °C:	105 mbar Source: butanone
Density and/or relative density:	
Density at 20 °C:	1,10 g/cm³
Relative vapour density:	not applicable
particle characteristics:	not applicable

9.2. Other information *

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

Article No.: 1 00028 T0000 epple 28 T / thixotropic
Print date 26.04.2023 Revision date 06.04.2023
Version 8.0 26.04.2023

EN
Page 6 / 10

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 *

Acute toxicity

butanone

oral, LD50, Rat: 2193 mg/kg

Method: OECD 403

dermal, LD50, Rabbit: 8050 mg/kg

Method: OECD 402

4-methylpentan-2-one

oral, LD50, Rat: 2080 mg/kg

Method: OECD 401

inhalative (vapours), LC50, Rat: 11 mg/L (4 h)

Method: OECD 403

dermal, LD 0:, Rat: > 2000 mg/kg

Method: OECD 402

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]

dermal, LD50, Rat: > 2000 mg/kg

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes serious eye irritation.

4-methylpentan-2-one

Skin, Rabbit (4 h): Evaluation no skin irritation

Method: OECD 404

eyes, Rabbit: Evaluation mild irritant.

Method: OECD 405

Respiratory or skin sensitisation

May cause an allergic skin reaction.

4-methylpentan-2-one

Skin, Guinea pig: ; Evaluation not sensitising.

Method: OECD 406

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Suspected of causing cancer.

4-methylpentan-2-one

Carcinogenicity; Evaluation Suspected of causing cancer.

Method: OECD 451

STOT-single exposure; STOT-repeated exposure

May cause drowsiness or dizziness.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 1 00028 T0000 epple 28 T / thixotropic
Print date 26.04.2023 Revision date 06.04.2023
Version 8.0 26.04.2023

EN
Page 7 / 10

aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. Toxicity

butanone

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 2993 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 308 mg/L (48 h)

Method: OECD 202

4-methylpentan-2-one

Fish toxicity, LC50, Danio rerio : > 179 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 200 mg/L (48 h)

Long-term Ecotoxicity

4-methylpentan-2-one

Daphnia toxicity, NOEC, Daphnia magna (Big water flea) 30 - 35 mg/L (21 d)

Method: OECD 211

semi-static test

12.2. Persistence and degradability

butanone

oxygen consumption: 98 % (28 d)

4-methylpentan-2-one

Biodegradation: 83 % (28 d); Evaluation Readily biodegradable

Method: OECD 301F

12.3. Bioaccumulative potential

butanone

Partition coefficient: n-octanol/water: 0,3

4-methylpentan-2-one

Partition coefficient: n-octanol/water: 1,9

Method: OECD 117

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 1 00028 T0000 epple 28 T / thixotropic
Print date 26.04.2023 Revision date 06.04.2023
Version 8.0 26.04.2023

EN
Page 8 / 10

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Observe in addition any national regulations!

List of proposed waste codes/waste designations in accordance with EWC

080409* Waste adhesives and sealants containing organic solvents or other dangerous substances
*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package

Dispose of packaging and contaminated filters at a official hazardous waste incinerator facility.

Recommendation:

Waste codes / waste designations according to EWC / AVV: 15 01 10*

Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1866

14.2. UN proper shipping name

Land transport (ADR/RID): Resin solution
Sea transport (IMDG): RESIN SOLUTION
Air transport (ICAO-TI / IATA-DGR): Resin solution

14.3. Transport hazard class(es)

3

14.4. Packing group

Land transport (ADR/RID):
for packages > 450 litres: III
Sea transport (IMDG):
for packages > 450 litres: II
Air transport (ICAO-TI / IATA-DGR):
for packages > 30 litres: III
II

14.5. Environmental hazards

Land transport (ADR/RID) not applicable
Marine pollutant not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.
Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code E
for packages > 450 litres: D/E
special prescription 640D

Sea transport (IMDG)

EmS-No. F-E, S-E

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 1 00028 T0000 epple 28 T / thixotropic
 Print date 26.04.2023 Revision date 06.04.2023
 Version 8.0 26.04.2023

EN
 Page 9 / 10

VOC-value (in g/L): 462

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Further details:

For professional use only. Product is not intended for consumer use.

Substance/product listed in the following inventories:

- AICS no information
- DSL no information
- EHS no information
- IECSC no information
- KECI no information
- MITI no information
- NZLoC no information
- PICCS no information
- TCSI no information
- TSCA no information

15.2. **Chemical Safety Assessment** *

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
203-550-1 108-10-1	4-methylpentan-2-one	01-2119473980-30
201-159-0 78-93-3	butanone	01-2119457290-43

SECTION 16: Other information *

Full text of classification in section 3

Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Carc. 2 / H351	Carcinogenicity	Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT RE 1 / H372	STOT-repeated exposure	Causes damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2	Flammable liquids	On basis of test data.
Eye Irrit. 2	Serious eye damage/eye irritation	Calculation method.
Skin Sens. 1	Respiratory or skin sensitisation	Calculation method.
Carc. 2	Carcinogenicity	Calculation method.
STOT SE 3	STOT-single exposure	Calculation method.

Abbreviations and acronyms

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 1 00028 T0000 epple 28 T / thixotropic
Print date 26.04.2023 Revision date 06.04.2023
Version 8.0 26.04.2023

EN
Page 10 / 10

OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version