

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 2 04851 NEU00 epple 4851  
Print date 11.04.2022 Revision date 12.01.2022  
Version 4.2 11.04.2022

EN  
Page 1 / 11

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Article No. (manufacturer/supplier): 2 04851 NEU00  
Trade name/designation epple 4851  
Adhesive

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses:**

Adhesive for the gluing of most diverse substrates.

**1.3. Details of the supplier of the safety data sheet**

**supplier (manufacturer/importer/downstream user/distributor)**

E. Epple & Co. GmbH

Hertzstr. 8

71083 Herrenberg

Telephone: +49 7032 / 9771-17

Telefax: +49 7032 / 9771-60

www.epple-chemie.de

**Department responsible for information:**

laboratory

E-mail (competent person)

labor@epple-chemie.de

**1.4. Emergency telephone number**

Information center against poisoning Bonn

+49 (0) 228 / 19 240 (Advice in German)

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2 / H225

Flammable liquids

Highly flammable liquid and vapour.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

Skin Sens. 1 / H317

Respiratory or skin sensitisation

May cause an allergic skin reaction.

STOT SE 3 / H336

STOT-single exposure

May cause drowsiness or dizziness.

Aquatic Chronic 2 / H411

Hazardous to the aquatic environment

Toxic to aquatic life with long lasting effects.

**2.2. Label elements**

The product is classified and labelled according to EC directives or corresponding national laws.

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



**Danger**

**Hazard statements**

H225

Highly flammable liquid and vapour.

H317

May cause an allergic skin reaction.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

H411

Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261

Avoid breathing vapours.

P280

Wear protective gloves.

P302 + P352

IF ON SKIN: Wash with plenty of soap and water.

P333 + P313

If skin irritation or rash occurs: Get medical advice/attention.

P501

Dispose of contents/container in accordance with local/regional/ national/international regulations.

**Hazard components for labelling**

rosin colophony

hydrocarbons, C7-C9, n-alkanes, iso-alkanes, cyclene

**Supplemental hazard information**

EUH066

Repeated exposure may cause skin dryness or cracking.

**2.3. Other hazards**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 2 04851 NEU00 epple 4851  
Print date 11.04.2022 Revision date 12.01.2022  
Version 4.2 11.04.2022

EN  
Page 2 / 11

No information available.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

**Description** polychloroprene solution

#### Hazardous ingredients

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

EC No.	REACH No.	weight-%
CAS No.	Designation	
Index No.	classification: // Remark	
920-750-0	01-2119473851-33 hydrocarbons, C7-C9, n-alkanes, iso-alkanes, cyclene STOT SE 3 H336 / Asp. Tox. 1 H304 / Aquatic Chronic 2 H411 / Flam. Liq. 2 H225	24,9 - 49,9
205-500-4	01-2119475103-46	
141-78-6	Ethyl acetate	24,9 - 49,9
607-022-00-5	Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	
204-658-1	01-2119485493-29	
123-86-4	n-butyl acetate	0,9 - 2,4
607-025-00-1	Flam. Liq. 3 H226 / STOT SE 3 H336	
232-475-7	01-2119480418-32	
8050-09-7	rosin colophony	0,9 - 2,4
650-015-00-7	Skin Sens. 1 H317	
215-222-5	01-2119463881-32	
1314-13-2	zinc oxide	0,1 - 0,9
030-013-00-7	Aquatic Acute 1 H400 / Aquatic Chronic 1 H410	
204-327-1	01-2119496065-33	
119-47-1	2,2-methylenebis(6-T-butyl-4-methylphenol) Repr. 2 H361 This substance has been listed as SVHC (substance of very high concern) in the Candidate List according to Article 59 of REACH.	0,1 - 0,9

#### Additional information

Full text of classification: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

##### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

##### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

##### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

##### Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

#### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

#### Unsuitable extinguishing media

strong water jet

### 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

### 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

### 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

### 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

#### Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Floors must be electrically conductive.

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

#### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

### Occupational exposure limit values

Ethyl acetate

Index No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

TWA: 730 mg/m<sup>3</sup>; 200 ppm

STEL: 1460 mg/m<sup>3</sup>; 400 ppm

n-butyl acetate

Index No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

TWA: 724 mg/m<sup>3</sup>; 150 ppm

STEL: 966 mg/m<sup>3</sup>; 200 ppm

### Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

### DNEL:

Ethyl acetate

Index No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

DNEL short-term oral (acute), Workers:

DNEL long-term dermal (systemic), Workers: 63 mg/kg bw/day

DNEL acute inhalative (local), Workers: 1468 mg/m<sup>3</sup>

DNEL acute inhalative (systemic), Workers: 1468 mg/m<sup>3</sup>

DNEL long-term inhalative (local), Workers: 734 mg/m<sup>3</sup>

DNEL long-term inhalative (systemic), Workers: 734 mg/m<sup>3</sup>

DNEL short-term oral (acute), Consumer:

DNEL long-term dermal (systemic), Consumer: 37 mg/kg bw/day

2,2-methylenebis(6-T-butyl-4-methylphenol)

EC No. 204-327-1 / CAS No. 119-47-1

DNEL short-term oral (acute), Workers: 1,59 mg/kg bw/day

DNEL long-term oral (repeated), Workers: 0,318 mg/kg bw/day

DNEL acute dermal, short-term (systemic), Workers: 1,8 mg/kg bw/day

DNEL long-term dermal (systemic), Workers: 0,36 mg/kg bw/day

DNEL acute inhalative (systemic), Workers: 6,25 mg/m<sup>3</sup>

DNEL long-term inhalative (systemic), Workers: 1,25 mg/m<sup>3</sup>

### PNEC:

Ethyl acetate

Index No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

PNEC aquatic, freshwater: 0,26 mg/L

PNEC aquatic, marine water: 0,026 mg/L

PNEC aquatic, intermittent release: 1,65 mg/L

PNEC sediment, freshwater: 1,25 mg/kg

PNEC sediment, marine water: 0,125 mg/kg

PNEC, soil: 0,24 mg/kg

PNEC sewage treatment plant (STP): 650 mg/L

2,2-methylenebis(6-T-butyl-4-methylphenol)

EC No. 204-327-1 / CAS No. 119-47-1

PNEC aquatic, freshwater: 6,8 µg/L

PNEC aquatic, marine water: 0,68 µg/L

PNEC sediment, freshwater: 102 mg/kg d.w.

PNEC sediment, marine water: 10,2 mg/kg d.w.

PNEC, soil: 20 mg/kg d.w.

PNEC sewage treatment plant (STP): 100 mg/L

PNEC Secondary Poisoning: 10 mg/kg food

## 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

### Personal protection equipment

#### Respiratory protection

Article No.: 2 04851 NEU00 epple 4851  
Print date 11.04.2022 Revision date 12.01.2022  
Version 4.2 11.04.2022

EN  
Page 5 / 11

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number. Recommendation: Half-face mask Filter type: ABEK-P2

#### **Hand protection**

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### **Eye/face protection**

Wear closely fitting protective glasses in case of splashes.

#### **Body protection**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

#### **Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

##### **Appearance:**

**Appearance:** Liquid  
**Colour:** white

**Odour:** like Solvents

**Odour threshold:** not applicable

**pH at 20 °C:** not relevant

**Melting point/freezing point:** -83 °C

Source: Ethyl acetate

**Initial boiling point and boiling range:** 77 °C

Source: Ethyl acetate

**Flash point:** -4 °C

**Evaporation rate:** 1,0 mg/s

Source: n-butyl acetate

##### **flammability**

**Burning time:** not applicable

##### **Upper/lower flammability or explosive limits:**

**Lower explosion limit:** 0,6 Vol-%  
Source: Ethyl acetate

**Upper explosion limit:** 12,8 Vol-%  
Source: Ethyl acetate

**Vapour pressure at 20 °C:** 98,4 mbar  
Source: Ethyl acetate

**Vapour density:** not applicable

**Relative density:**  
**Density at 20 °C:** 0,87 g/cm<sup>3</sup>

**Solubility(ies):**  
**Water solubility at 20 °C:** insoluble

**Partition coefficient: n-octanol/water:** see section 12

**Auto-ignition temperature:** 246 °C  
Source: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

**Decomposition temperature:** not applicable

**Viscosity at °C:** 2 - 4,5 Pa\*s

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 2 04851 NEU00 epple 4851  
Print date 11.04.2022 Revision date 12.01.2022  
Version 4.2 11.04.2022

EN  
Page 6 / 11

**Explosive properties:** not applicable  
**Oxidising properties:** not applicable

9.2. **Other information**

**SECTION 10: Stability and reactivity**

10.1. **Reactivity**

No information available.

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

not applicable

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

**SECTION 11: Toxicological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

11.1. **Information on toxicological effects**

**Acute toxicity**

Ethyl acetate

oral, LD50, Rat: > 2000 mg/kg  
dermal, LD50, Rabbit: > 18000 mg/kg  
inhalative (vapours), LC50, Rat: > 22,5 mg/L (6 h)

rosin colophony

oral, LD50, Rat: > 2000 mg/kg  
dermal, LD50, Rat: > 2000 mg/kg

Formaldehyde, polymer with 4-(1,1-dimethylethyl)phenol

oral, LD50, Rat: > 5000 mg/kg  
dermal, LD50, Rabbit: > 2000 mg/kg

2,2-methylenebis(6-T-butyl-4-methylphenol)

oral, LD50, Rat: > 5000 mg/kg  
dermal, LD50, Rabbit: > 10000 mg/kg

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

oral, LD50, Rat: > 5840 mg/kg  
Method: OECD 401  
dermal, LD50, Rat: > 2920 mg/kg  
Method: OECD 402  
inhalative (vapours), LC50, Rat: 23,3 mg/L (4 h)  
Method: OECD 403

**Skin corrosion/irritation; Serious eye damage/eye irritation**

Causes serious eye irritation.

Ethyl acetate

eyes, Rabbit: Evaluation mild irritant.  
Method: OECD 405  
Skin, Rabbit (4 h): Evaluation non-irritant.

2,2-methylenebis(6-T-butyl-4-methylphenol)

Skin, Rabbit: Evaluation non-irritant.  
Method: OECD 404  
Eyes:, Rabbit: Evaluation no eye irritation  
Method: OECD 405

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 2 04851 NEU00 epple 4851  
Print date 11.04.2022 Revision date 12.01.2022  
Version 4.2 11.04.2022

EN  
Page 7 / 11

### Respiratory or skin sensitisation

May cause an allergic skin reaction.

Ethyl acetate

Skin, Guinea pig: ; Evaluation not sensitising.

Method: OECD 406

rosin colophony

Skin: ; Evaluation May cause sensitization by skin contact.

2,2-methylenebis(6-T-butyl-4-methylphenol)

Skin, human.: ; Evaluation not sensitising.

Method: patch test

### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

2,2-methylenebis(6-T-butyl-4-methylphenol)

Germ cell mutagenicity; Evaluation negative

Method: OECD 471 (Ames test)

genotoxicity; Evaluation negative

Method: OECD 471 (Ames test)

Salmonella typhimurium; in-vitro

genotoxicity; Evaluation negative

Method: OECD 471 (Ames test)

Escherichia coli; in-vitro

genotoxicity; Evaluation negative

Method: OECD 473

in-vitro

genotoxicity; Evaluation negative

Method: OECD 476

in-vitro

### STOT-single exposure; STOT-repeated exposure

May cause drowsiness or dizziness.

### Aspiration hazard

Based on available data, the classification criteria are not met.

### Practical experience/human evidence

### Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

### Remark

There is no information available on the preparation itself.

## SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

### 12.1. Toxicity

Ethyl acetate

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 230 mg/L (96 h)

Bacteria toxicity, NOEC, Pseudomonas putida: 650 mg/L (16 h)

rosin colophony

Fish toxicity, LC50, Danio rerio (zebrafish):  $\geq 1$  mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 911 mg/L (48 h)

Algae toxicity, EC50, Scenedesmus subspicatus: 410 mg/L (72 h)

2,2-methylenebis(6-T-butyl-4-methylphenol)

Fish toxicity, LC50, Oryzias latipes (Ricefish):  $> 5$  mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea):  $> 4,8$  mg/L (48 h)

Method: OECD 202

Algae toxicity, EC50, Pseudokirchneriella subcapitata:  $> 5$  mg/L (72 h)

Method: OECD 201

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics  
Fish toxicity, LL50, Oncorhynchus mykiss (Rainbow trout): 13,4 mg/L (96 h)  
Algae toxicity, EL50, Pseudokirchneriella subcapitata 10 - 30 mg/L (72 h)  
Daphnia toxicity, EL50, Daphnia magna: 3 mg/L (48 h)  
Daphnia toxicity, NOELR, Pseudokirchneriella subcapitata: 10 mg/L (72 h)

#### Long-term Ecotoxicity

Toxic to aquatic life with long lasting effects.

##### Ethyl acetate

Fish toxicity, NOEC, Pimephales promelas (fathead minnow): < 9,65 mg/L (32 d)  
Daphnia toxicity, NOEC, Daphnia magna: 2,4 mg/L (21 d)  
Bacteria toxicity, NOEC, Pseudomonas putida: 650 mg/L (16 h)  
Method: DIN 38412

##### 2,2-methylenebis(6-T-butyl-4-methylphenol)

Daphnia toxicity, NOEC, Daphnia magna (Big water flea): 0,34 mg/L (21 d)  
Method: OECD 211  
Algae toxicity, NOEC, Pseudokirchneriella subcapitata: 1,3 mg/L (72 h)  
Method: OECD 201

##### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Daphnia toxicity, NOELR, Daphnia magna: 1 mg/L (21 day(s))  
Daphnia toxicity, EL50, Daphnia magna: 1,6 mg/L (21 day(s))

#### 12.2. Persistence and degradability

##### Ethyl acetate

Biodegradation, aerobic: 69 % (20 d); Evaluation Readily biodegradable

##### 2,2-methylenebis(6-T-butyl-4-methylphenol)

Biodegradation: (28 d) Evaluation not biodegradable  
Method: OECD 301C

##### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Biodegradation: 81 % (28 d)

#### 12.3. Bioaccumulative potential

##### 2,2-methylenebis(6-T-butyl-4-methylphenol)

Partition coefficient: n-octanol/water: 6,25

##### Bioconcentration factor (BCF)

##### Ethyl acetate

Bioconcentration factor (BCF), Leuciscus idus (golden orfe): 30

##### 2,2-methylenebis(6-T-butyl-4-methylphenol)

Bioconcentration factor (BCF): 840

#### 12.4. Mobility in soil

Toxicological data are not available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

No information available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

##### List of proposed waste codes/waste designations in accordance with EWC

080409\* Waste adhesives and sealants containing organic solvents or other dangerous substances

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

##### Appropriate disposal / Package



**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 2 04851 NEU00 epple 4851  
Print date 11.04.2022 Revision date 12.01.2022  
Version 4.2 11.04.2022

EN  
Page 9 / 11

**Dispose of packaging and contaminated filters at a official hazardous waste incinerator facility.**

Recommendation:

Waste codes / waste designations according to EWC / AVV: 15 01 10\*

#### SECTION 14: Transport information

**14.1. UN number**

UN 1133

**14.2. UN proper shipping name**

Land transport (ADR/RID):

Adhesives  
mixture

Sea transport (IMDG):

ADHESIVES  
MIXTURE

Air transport (ICAO-TI / IATA-DGR):

Adhesives  
mixture

**14.3. Transport hazard class(es)**

3

**14.4. Packing group**

Land transport (ADR/RID):

III

for packages > 450 litres:

II

Sea transport (IMDG):

III

for packages > 450 litres

II

Air transport (ICAO-TI / IATA-DGR):

II

**14.5. Environmental hazards**

Land transport (ADR/RID)

DANGEROUS FOR THE ENVIRONMENT

Marine pollutant

p

**14.6. Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Further information**

**Land transport (ADR/RID)**

tunnel restriction code

D/E

for packages > 450 litres:

E

special prescription 640D

**Sea transport (IMDG)**

EmS-No.

F-E, S-D

**Air transport (ICAO-TI / IATA-DGR)**

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

#### SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]**

VOC-value (in g/L): 630

**National regulations**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

**Substance/product listed in the following inventories:**

AICS no information

DSL no information

IECSC no information

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2015/830**



Article No.: 2 04851 NEU00 epple 4851  
 Print date 11.04.2022 Revision date 12.01.2022  
 Version 4.2 11.04.2022

EN  
 Page 10 / 11

KECI no information  
 MITI no information  
 PICCS no information  
 TSCA no information

**15.2. Chemical Safety Assessment**

**For the following substances of this mixture a chemical safety assessment has been carried out:**

EC No. CAS No.	Designation	REACH No.
920-750-0	hydrocarbons, C7-C9, n-alkanes, iso-alkanes, cyclene	01-2119473851-33
205-500-4 141-78-6	Ethyl acetate	01-2119475103-46
204-658-1 123-86-4	n-butyl acetate	01-2119485493-29
232-475-7 8050-09-7	rosin colophony	01-2119480418-32
215-222-5 1314-13-2	zinc oxide	01-2119463881-32
204-327-1 119-47-1	2,2-methylenebis(6-T-butyl-4-methylphenol)	01-2119496065-33

**SECTION 16: Other information**

**Full text of classification in section 3**

STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic organisms.
Aquatic Chronic 1 / H410	Hazardous to the aquatic environment	Very toxic to aquatic life with long lasting effects.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).

**Classification procedure**

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2	Flammable liquids	On basis of test data.
Eye Irrit. 2	Serious eye damage/eye irritation	Calculation method.
Skin Sens. 1	Respiratory or skin sensitisation	Calculation method.
STOT SE 3	STOT-single exposure	Calculation method.
Aquatic Chronic 2	Hazardous to the aquatic environment	Calculation method.

**Abbreviations and acronyms**

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 2 04851 NEU00 epple 4851  
Print date 11.04.2022 Revision date 12.01.2022  
Version 4.2 11.04.2022

EN  
Page 11 / 11

---

IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

**Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.