acco		egulation (EO) 20	120/070		epple
Article Print o Versio	date	2 05621 AN000 07.03.2023 5.0	epple-easy 5621-n Revision date 07.0 07.03.2023		EN Page 1 / 9
SEC	TION 1: Id	entification of th	e substance/mixtu	re and of the compa	ny/undertaking
1.1.	Product id	lentifier			
		(manufacturer/supp e/designation	olier):	2 05621 AN000 epple-easy 5621-new Adhesive Component A UFI: EHF0-Q0E6-300	
1.2.	Relevant i	dentified uses of t	he substance or mix	ture and uses advised	d against
		dentified uses: or the gluing of mos	t diverse substrates.		
1.3.	Details of	the supplier of the	safety data sheet		
		nanufacturer/impo Co. GmbH	orter/downstream us	er/distributor)	
	Hertzstr. 8			Telephone: +49 7032 / Telefax: +49 7032 / 97	
	71083 Heri	enberg		www.epple-chemie.de	
	Departme laboratory	nt responsible for	information:		
		npetent person)		labor@epple-chemie.c	de
1.4.		y telephone numb n center against pois		+49 (0) 228 / 19 240 (/	Advice in German)
SEC	TION 2: Ha	azards identificat	tion		
2.1.	Classificat	tion of the substar	nce or mixture		
	Classificat	tion according to I	Regulation (EC) No 1	272/2008 [CLP]	
	The mixtur	e is classified as ha	zardous according to	regulation (EC) No 127	2/2008 [CLP].
	Skin Irrit. 2		Skin corrosion/irritat		Causes skin irritation.
	Eye Irrit. 2 Skin Sens.		Serious eye damag Respiratory or skin		Causes serious eye irritation. May cause an allergic skin reaction.
	Aquatic Ch	ronic 2 / H411	Hazardous to the ad		Toxic to aquatic life with long lasting effects.

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Warning

Hazard statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.
Precautionary state	ements
P261	Avoid breathing vapours.
P280	Wear protective gloves.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container in accordance with local/regional/ national/international regulations.
Hazard components	s for labelling
	bis-[4-(2,3-epoxipropoxi)phenyl]propane
	Bisphenol-F-epichlorohydrin resin with molecular weight <= 700

Supplemental hazard information

Contains epoxy constituents. May produce an allergic reaction.

EUH205 2.3. Other hazards



Article No.:	2 05621 AN000	epple-easy 5621-new
Print date	07.03.2023	Revision date 07.03.2023
Version	5.0	07.03.2023

No information available.

Mixtures		
Description	branched polyalcohol, filled	
Hazardous ingr	edients	
Classification a	ccording to Regulation (EC) No 1272/2008 [CLP]	
EC No. CAS No. Index No.	REACH No. Designation classification: // Remark	weight-%
216-823-5 1675-54-3 603-073-00-2	01-2119456619-26 bis-[4-(2,3-epoxipropoxi)phenyl]propane Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Aquatic Chronic 2 H411 Specific concentration limit (SCL): Eye Irrit. 2 H319 >= 5 / Skin Irrit. 2 H315 >= 5	74,9 - 100
500-006-8 9003-36-5	01-2119454392-40 Bisphenol-F-epichlorohydrin resin with molecular weight <= 700 Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Aquatic Chronic 2 H411	9,9 - 19,9

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. **Most important symptoms and effects, both acute and delayed** In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.



Article No.:	2 05621 AN000	epple-easy 5621-new
Print date	07.03.2023	Revision date 07.03.2023
Version	5.0	07.03.2023

EN Page 3 / 9

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

not applicable

DNEL:

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Index No. 603-073-00-2 / EC No. 216-823-5 / CAS No. 1675-54-3

DNEL acute dermal, short-term (systemic), Workers: 8,3 mg/kg bw/day

DNEL long-term dermal (systemic), Workers: 8,3 mg/kg bw/day

DNEL acute inhalative (systemic), Workers: 12,3 mg/m³

DNEL long-term inhalative (systemic), Workers: 12,3 mg/m³

Bisphenol-F-epichlorohydrin resin with molecular weight <= 700

EC No. 500-006-8 / CAS No. 9003-36-5

DNEL acute dermal, short-term (local), Workers: 8,3 µg/cm³

- DNEL long-term dermal (systemic), Workers: 104,15 mg/kg bw/day
- DNEL long-term inhalative (systemic), Workers: 29,39 mg/m³

PNEC:

bis-[4-(2,3-epoxipropoxi)phenyl]propane



Article No.:	2 05621 AN000	epple-easy 5621-new
Print date	07.03.2023	Revision date 07.03.2023
Version	5.0	07.03.2023

Index No. 603-073-00-2 / EC No. 216-823-5 / CAS No. 1675-54-3 PNEC aquatic, freshwater: 6 µg/L PNEC aquatic, intermittent release: 0,013 mg/L PNEC sediment, freshwater: 0,996 mg/kg dw PNEC sediment, marine water: 0,1 mg/kg dw PNEC, soil: 0,196 mg/kg dw PNEC, soil: 0,196 mg/kg dw PNEC sewage treatment plant (STP): 10 mg/L Bisphenol-F-epichlorohydrin resin with molecular weight <= 700 EC No. 500-006-8 / CAS No. 9003-36-5 PNEC aquatic, freshwater: 0,003 mg/L PNEC aquatic, marine water: 0,003 mg/L PNEC aquatic, intermittent release: 0,0254 mg/L PNEC sediment, freshwater: 0,294 mg/kg bw/day

PNEC sediment, marine water: 0,0294 mg/kg bw/day

PNEC, soil: 0,237 mg/kg bw/day

PNEC sewage treatment plant (STP): 10 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

Recommendation: full mask / half mask / filtering half mask. Type A / B class 1/2Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Appearance:	Liquid
Colour:	colourless
Odour:	characteristic
Odour threshold:	not applicable
Melting point/freezing point:	8 °C
	Source: bis-[4-(2,3-epoxipropoxi)phenyl]propane
Initial boiling point and boiling range:	not applicable
Flammability:	Combustible liquid.
Lower and upper explosion limit:	
Lower explosion limit:	not applicable
Upper explosion limit:	not applicable



Article Print d Versio	ate	2 05621 AN000 07.03.2023 5.0	epple-easy 562 Revision date 0 07.03.2023			EN Page 5 / 9		eppie
	Flash poir	it:		95 °C				
	-	ion temperature:		not applicable				
	Decompos	sition temperature:		not applicable				
	pH at 20 °C: Cinematic viscosity (40°C):		not relevant					
				42735,04 mm²/s				
	Viscosity	at 20 °C:		35 - 65 Pa*s				
	Solubility(Water sol	ies): ubility at 20 °C:		insoluble				
	Partition c	oefficient: n-octan	ol/water:	see section 12				
	Vapour pr	essure at 20 °C:		not applicable				
	Density ar Density a	nd/or relative densi t 20 °C:	ty:	1,17 g/cm ³				
	-	apour density:		not applicable				
	particle ch	aracteristics:		not applicable				
9.2.	Other info	rmation						
	Solvent se	paration test:		< 3 weight-% (AD	DR/RID)			
SECT	FION 10: S	Stability and react	ivity					
	Reactivity							
		tion available.						
10.2.	Chemical Stable whe section 7.	-	mmended regulat	ions for storage an	d handling. Fu	urther inform	ation on co	rrect storage: refer to
10.3.	-	of hazardous read from strong acids, s		strong oxidizing ag	ents to avoid	exothermic r	eactions.	
10.4.	Condition Hazardous	s to avoid decomposition byp	roducts may form	with exposure to hi	igh temperatu	res.		
10.5.	Incompati not applica	ble materials ble						
10.6.	Hazardous	s decomposition pr decomposition byp ogen oxides.		i with exposure to h	nigh temperatu	ures, e.g.: ca	arbon dioxic	le, carbon monoxide
SECT	FION 11: T	oxicological info	rmation					
11.1.	Informatio	n on hazard classe	s as defined in F	Regulation (EC) No	o 1272/2008			
	Acute toxi	city						
	oral, LD5 dermal, L Method:	epoxipropoxi)pheny 0, Rat: > 2000 mg/kg D50, Rat: > 2000 mg OECD 402 D50, Rabbit: > 2000	g g/kg					
	oral, LD5	F-epichlorohydrin re 0, Rat: > 2000 mg/kg D50, Rabbit: > 2000	g	r weight <= 700				
	Skin corro	sion/irritation; Ser	ious eye damage	e/eye irritation				
	Skin corro Causes sk		ious eye damage	e/eye irritation				
	Causes sk		ious eye damage	e/eye irritation				

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.



Article No.:	2 05621 AN000	epple-easy 5621-new
Print date	07.03.2023	Revision date 07.03.2023
Version	5.0	07.03.2023

STOT-single exposure; STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Based on the properties of the epoxy constituents and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and an irritant. It contains low molecular weight epoxy constituents which are irritating to eyes, mucous membrane and skin. Repeated skin contact may result in irritations and sensitizations, possibly due to a cross-over sensitization with other epoxy compounds. Skin contact with the preparation and exposure to spray mist and vapour should be avoided.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP] Do not allow to enter into surface water or drains.

12.1. Toxicity

bis-[4-(2,3-epoxipropoxi)phenyl]propane Fish toxicity, LC50: 1,3 mg/L (96 h) Method: OECD 203 Daphnia toxicity, EC50: 2,1 mg/L (48 h) Method: OECD 202

Bisphenol-F-epichlorohydrin resin with molecular weight <= 700 Fish toxicity, LC50: 2,54 mg/L (96 h) Daphnia toxicity, EC50: 2,55 mg/L (48 h) Algae toxicity, EC50: > 1000 mg/L (72 h)

Long-term Ecotoxicity

Toxic to aquatic life with long lasting effects.

bis-[4-(2,3-epoxipropoxi)phenyl]propane Daphnia toxicity, NOEC: 0,3 mg/L (21 d) Method: OECD 211

12.2. Persistence and degradability

bis-[4-(2,3-epoxipropoxi)phenyl]propane
Biodegradation:: 5 % (28 d); Evaluation Not readily biodegradable (according to OECD criteria)
Method: OECD 301F
Biodegradation:: 6 - 12 % (28 d); Evaluation Not readily biodegradable (according to OECD criteria)
Method: OECD 301B

12.3. Bioaccumulative potential

bis-[4-(2,3-epoxipropoxi)phenyl]propane Partition coefficient: n-octanol/water: 2,64 - 3,78 Bisphenol-F-epichlorohydrin resin with molecular weight <= 700 Partition coefficient: n-octanol/water: 3,3

Bioconcentration factor (BCF)

bis-[4-(2,3-epoxipropoxi)phenyl]propane Bioconcentration factor (BCF): 3 - 31

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment



Article No.:	2 05621 AN000	epple-easy 5621-new
Print date	07.03.2023	Revision date 07.03.2023
Version	5.0	07.03.2023

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available. 12.7. **Other adverse effects**

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080409* Waste adhesives and sealants containing organic solvents or other dangerous substances *Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number or ID number

14.1.		UN 3082			
14.2	UN proper shipping name				
	Land transport (ADR/RID):	Environmentally hazardous substance, liquid, n.o.s. (4,4'-methylene diphenyl diglycidyl ether)			
	Sea transport (IMDG):	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4,4'-methylene diphenyl diglycidyl ether)			
	Air transport (ICAO-TI / IATA-DGR):	Environmentally hazardous substance, liquid, n.o.s. (4,4'-methylene diphenyl diglycidyl ether)			
14.3.	Transport hazard class(es)				
		9			
14.4.	Packing group				
		III			
14.5.	Environmental hazards				
	Land transport (ADR/RID)	DANGEROUS FOR THE ENVIRONMENT			
	Marine pollutant	p / 4,4'-methylene diphenyl diglycidyl ether			
14.6.	Special precautions for user				
	Transport always in closed, upright and safe con case of an accident or leakage. Advices on safe handling: see parts 6 - 8	tainers. Make sure that persons transporting the product know what to do in			
	Further information				
	Land transport (ADR/RID)				
	Tunnel restriction code	-			
	in packages <= 5 litres	KEIN GUT DER KLASSE 9			
	Sea transport (IMDG)				
	EmS-No.	F-A, S-F			
	in packages <= 5 litres	NOT RESTRICTED 2.10.2.7			
	Air transport (ICAO-TI / IATA-DGR)				
	in packages <= 5 litres	NOT RESTRICTED			
14.7.	Maritime transport in bulk according to IMO i	nstruments			
	No transport as bulk according IBC - Code.				



Print date 07.03.2023 Revision date 07.03.2023 Version 5.0 07.03.2023				
---	--	--	--	--

EN Page 8 / 9

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 0

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Substance/product listed in the following inventories:

AICS listed DSL listed EHS no information IECSC listed KECI listed MITI listed NZLoC no information PICCS listed TCSI no information TSCA listet

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No.	Designation	REACH No.
CAS No.		
216-823-5 1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane	01-2119456619-26
500-006-8 9003-36-5	Bisphenol-F-epichlorohydrin resin with molecular weight <= 700	01-2119454392-40

SECTION 16: Other information

Full text of classification in section 3:								
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.						
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.						
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.						
Aquatic Chronic 2 / H41	1 Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.						
Classification procedure								
Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]								
Skin Irrit. 2	Skin corrosion/irritation	Calculation method.						
Eye Irrit. 2	Serious eye damage/eye irritation	Calculation method.						
Skin Sens. 1	Respiratory or skin sensitisation	Calculation method.						
Aquatic Chronic 2	Hazardous to the aquatic environment	Calculation method.						
Abbreviations and acronyms								
ADR E	European Agreement concerning the International Carriage of Dangerous Goods by Road							
OEL C	Occupational Exposure Limit Value							
BLV B	Biological Limit Value							
CAS C	Chemical Abstracts Service							
CLP C	Classification, Labelling and Packaging							
CMR C	Carcinogenic, Mutagenic and Reprotoxic							
DIN G	German Institute for Standardization / German industrial standard							
DNEL D	Derived No-Effect Level							
EAKV E	European Waste Catalogue Directive							
EC E	Effective Concentration							
EC E	European Community							
	European Standard							



Article No.: Print date Version	2 05621 AN000 07.03.2023 5.0	epple-easy 5621-new Revision date 07.03.2023 07.03.2023	EN Page 9 / 9		
IBC Code	Internatio	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk			
ICAO-TI		International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air			
IMDG Code	e Internatio	International Maritime Code for Dangerous Goods			
ISO	Internatio	International Organization for Standardization			
LC	Lethal C	Lethal Concentration			
LD	Lethal D	Lethal Dose			
MARPOL	Maritime	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships			
OECD	Organisa	Organisation for Economic Cooperation and Development			
PBT	persister	persistent, bioaccumulative, toxic			
PNEC	Predicte	Predicted No Effect Concentration			
REACH	Registra	Registration, Evaluation, Authorisation and Restriction of Chemicals			
RID	Regulati	Regulations concerning the International Carriage of Dangerous Goods by Rail			
UN	United N	United Nations			
VOC	Volatile	Volatile Organic Compounds			
vPvB	very pers	very persistent and very bioaccumulative			
ALL					

Abbreviations and acronyms

n.a. = not applicable

n.b. = not determined

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations.Without written approval, the product must not be used for purposes different from those mentioned in section 1.It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version