

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 4 06789 B00V1 epple 06789-new / V1
Print date 11.05.2023 Revision date 11.05.2023
Version 7.0 11.05.2023

EN
Page 1 / 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier): 4 06789 B00V1
Trade name/designation epple 06789-new / V1
cast resin
component B
UFI: 3T40-H0EA-G004-V4R9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Casting resin for casting electronic and other components.

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

E. Epple & Co. GmbH
Hertzstr. 8
71083 Herrenberg

Telephone: +49 7032 / 9771-17
Telefax: +49 7032 / 9771-60
www.epple-chemie.de

Department responsible for information:

laboratory

E-mail (competent person)

labor@epple-chemie.de

1.4. Emergency telephone number

Information center against poisoning Bonn +49 (0) 228 / 19 240 (Advice in German)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Skin Corr. 1B / H314	Skin corrosion/irritation	Causes severe skin burns and eye damage.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe vapour.
P280 Wear protective gloves.
P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents / container to a certified waste management company.

Hazard components for labelling

reaction product of m-phenylenebis(methylamine) and 4,4'-Isopropylidenediphenol, oligomeric
reaction product with 1-chloro-2,3-epoxypropane
Reaction products of 3-aminomethyl-3,5,5-trimethylcyclohexylamine and 4,4'-isopropylidenediphenol,
oligomeric
Reaction product with 1-chloro-2,3-epoxypropane
Trimethylhexan-1,6-diamin

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 4 06789 B00V1 epple 06789-new / V1
 Print date 11.05.2023 Revision date 11.05.2023
 Version 7.0 11.05.2023

EN
 Page 2 / 11

3-aminomethyl-3,5,5-trimethyl-cyclohexylamine

Supplemental hazard information

not applicable

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description modified aminic hardener

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification: // Remark	weight-%
500-302-7 113930-69-1	01-2119965162-39 reaction product of m-phenylenebis(methylamine) and 4,4'-Isopropylidenediphenol, oligomeric reaction product with 1-chloro.2,3-epoxypropane	24,9 - 49,9
	Skin Corr. 1B H314 / Eye Dam. 1 H318 / Skin Sens. 1 H317 / Aquatic Chronic 2 H411	
202-859-9 100-51-6 603-057-00-5	01-2119492630-38 benzyl alcohol	24,9 - 49,9
	Acute Tox. 4 H332 / Acute Tox. 4 H302 Acute toxicity estimate (ATE): ATE (oral): 1230 mg/kg bw / ATE (inhalation, vapour): 4,17 mg/L	
500-101-4 38294-64-3	01-2119965165-33 Reaction products of 3-aminomethyl-3,5,5-trimethylcyclohexylamine and 4,4'-isopropylidenediphenol, oligomeric Reaction product with 1-chloro-2,3-epoxypropane	9,9 - 19,9
	Skin Corr. 1B H314 / Skin Sens. 1A H317 / Aquatic Chronic 3 H412	
247-134-8 25620-58-0	01-2119560598-25 Trimethylhexan-1,6-diamin	9,9 - 19,9
	Acute Tox. 4 H302 / Skin Corr. 1B H314 / Skin Sens. 1 H317 / Aquatic Chronic 3 H412 Acute toxicity estimate (ATE): ATE (oral): 910 mg/kg bw	
220-666-8 2855-13-2 612-067-00-9	01-2119514687-32 3-aminomethyl-3,5,5-trimethyl-cyclohexylamine	2,4 - 9,9
	Acute Tox. 4 H302 / Skin Corr. 1B H314 / Eye Dam. 1 H318 / Skin Sens. 1A H317 Specific concentration limit (SCL): Skin Sens. 1A H317 >= 0,001 Acute toxicity estimate (ATE): ATE (oral): 1030 mg/kg bw	
9046-10-0	01-2119557899-12 Polyoxypropylen diamine	2,4 - 9,9
	Skin Corr. 1C H314 / Aquatic Chronic 3 H412	

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrsiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 4 06789 B00V1 epple 06789-new / V1
Print date 11.05.2023 Revision date 11.05.2023
Version 7.0 11.05.2023

EN
Page 4 / 11

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. **Specific end use(s)**

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

*

Occupational exposure limit values

not applicable

DNEL:

benzyl alcohol

Index No. 603-057-00-5 / EC No. 202-859-9 / CAS No. 100-51-6

DNEL acute dermal, short-term (systemic), Workers: 47 mg/kg bw/day

DNEL long-term dermal (systemic), Workers: 9,5 mg/kg

DNEL acute inhalative (systemic), Workers: 450 mg/m³

DNEL long-term inhalative (systemic), Workers: 90 mg/m³

3-aminomethyl-3,5,5-trimethyl-cyclohexylamine

Index No. 612-067-00-9 / EC No. 220-666-8 / CAS No. 2855-13-2

DNEL long-term inhalative (local), Workers: 0,073 mg/m³

reaction product of m-phenylenebis(methylamine) and 4,4'-Isopropylidenediphenol, oligomeric reaction product with 1-chloro.2,3-epoxypropane

EC No. 500-302-7 / CAS No. 113930-69-1

DNEL long-term dermal (systemic), Workers: 0,14 mg/kg bw/day

DNEL long-term inhalative (systemic), Workers: 0,493 mg/m³

PNEC:

benzyl alcohol

Index No. 603-057-00-5 / EC No. 202-859-9 / CAS No. 100-51-6

PNEC aquatic, freshwater: 1 mg/L

PNEC aquatic, marine water: 0,1 mg/L

PNEC aquatic, intermittent release: 2,3 mg/L

PNEC sediment, freshwater: 5,27 mg/kg

PNEC sediment, marine water: 0,527 mg/kg

PNEC, soil: 0,456 mg/kg

PNEC sewage treatment plant (STP): 39 mg/L

3-aminomethyl-3,5,5-trimethyl-cyclohexylamine

Index No. 612-067-00-9 / EC No. 220-666-8 / CAS No. 2855-13-2

PNEC aquatic, freshwater: 0,06 mg/L

PNEC aquatic, marine water: 0,006 mg/L

PNEC aquatic, intermittent release: 0,23 mg/L

PNEC sediment, freshwater: 5,784 mg/kg

PNEC sediment, marine water: 0,578 mg/kg

PNEC sewage treatment plant (STP): 3,18 mg/L

Trimethylhexan-1,6-diamin

EC No. 247-134-8 / CAS No. 25620-58-0

PNEC aquatic, freshwater: 0,102 mg/L

PNEC aquatic, marine water: 0,01 mg/L

PNEC sediment, freshwater: 0,662 mg/kg

PNEC sediment, marine water: 0,062 mg/kg

PNEC sewage treatment plant (STP): 72 mg/L

reaction product of m-phenylenebis(methylamine) and 4,4'-Isopropylidenediphenol, oligomeric reaction product with 1-chloro.2,3-epoxypropane

EC No. 500-302-7 / CAS No. 113930-69-1

PNEC aquatic, freshwater: 0,001 mg/L

PNEC aquatic, marine water: 0,0001 mg/L

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 4 06789 B00V1 epple 06789-new / V1
Print date 11.05.2023 Revision date 11.05.2023
Version 7.0 11.05.2023

EN
Page 5 / 11

PNEC sediment, freshwater: 0,007 mg/kg
PNEC sediment, marine water: 0,0007 mg/kg
PNEC sewage treatment plant (STP): 8,889 mg/L
PNEC Secondary Poisoning: 3,33 mg/kg

8.2. Exposure controls

*

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If the workplace limit values (AGW) are exceeded, a suitable breathing apparatus must be worn. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Use filter / combination filter according to EN 14387.

Suitable respiratory protection apparatus: ABEK-P2

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear eye glasses with side protection according to EN 166.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Appearance:	Liquid
Colour:	yellow
Odour:	Amines
Odour threshold:	not applicable
Melting point/freezing point:	-80 °C Source: Trimethylhexan-1,6-diamin
Initial boiling point and boiling range:	206 °C Source: benzyl alcohol
Flammability:	Combustible liquid.
Lower and upper explosion limit:	
Lower explosion limit:	1,22 Vol-% Source: benzyl alcohol
Upper explosion limit:	13 Vol-% Source: benzyl alcohol
Flash point:	94 °C
Auto-ignition temperature:	435 °C Source: benzyl alcohol
Decomposition temperature:	not applicable
pH at 20 °C:	not relevant
Cinematic viscosity (40°C):	95,24 mm²/s

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 4 06789 B00V1 epple 06789-new / V1
Print date 11.05.2023 Revision date 11.05.2023
Version 7.0 11.05.2023

EN
Page 6 / 11

Viscosity at 20 °C: 100 mPa* s
Solubility(ies):
Water solubility at 20 °C: partially miscible
Partition coefficient: n-octanol/water: see section 12
Vapour pressure at 20 °C: 0,027 mbar
Source: benzyl alcohol
Density and/or relative density:
Density at 20 °C: 1,05 g/cm³
Relative vapour density: not applicable
particle characteristics: not applicable

9.2. **Other information**

Solvent separation test: < 3 weight-% (ADR/RID)

SECTION 10: Stability and reactivity

10.1. **Reactivity**

No information available.

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

not applicable

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. **Information on hazard classes as defined in Regulation (EC) No 1272/2008** *

Acute toxicity

benzyl alcohol

oral, LD50, Rat: 1230 mg/kg

dermal, LD50, Rabbit: 2000 mg/kg

inhalative (Gases), LC50, Rat: > 4,178 ppmV (4 h)

3-aminomethyl-3,5,5-trimethyl-cyclohexylamine

oral, LD50, Rat: 1030 mg/kg

dermal, LD50, Rat: > 2000 mg/kg

Trimethylhexan-1,6-diamin

oral, LD50, Rat: 910 mg/kg

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes severe skin burns and eye damage.

benzyl alcohol

eyes, Rabbit: Evaluation Irritating to eyes.

Method: OECD 405

Skin, Rabbit: Evaluation no skin irritation

Method: OECD 404

Trimethylhexan-1,6-diamin

Skin, Mouse: Evaluation corrosive

Skin, Rabbit: Evaluation irritant.

eyes, Rabbit: Evaluation corrosive

Method: OECD 405

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 4 06789 B00V1 epple 06789-new / V1
Print date 11.05.2023 Revision date 11.05.2023
Version 7.0 11.05.2023

EN
Page 7 / 11

Respiratory or skin sensitisation

May cause an allergic skin reaction.

benzyl alcohol

Skin, Guinea pig: ; Evaluation not sensitising.

Method: OECD 406

Trimethylhexan-1,6-diamin

Skin, Guinea pig: ; Evaluation sensitising

Method: OECD 406

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Trimethylhexan-1,6-diamin

Reproductive toxicity; Evaluation No effect on fertility and early embryonic development was observed.

Method: OECD 416

oral; Rat

genotoxicity; Evaluation negative

Method: 67/548/EEC, appendix V, B.13/14 (Ames test).

in-vitro

genotoxicity; Evaluation negative

Method: OECD 473

in-vitro

genotoxicity; Evaluation negative

Method: OECD 476

in-vitro

genotoxicity; Evaluation negative

Method: OECD 474

in-vivo; oral.; Hamster

genotoxicity; Evaluation negative

Method: OECD 474

in-vivo; oral; Mouse

Reproductive toxicity.; Evaluation No mutagenic effect

Rabbit; oral

STOT-single exposure; STOT-repeated exposure

Trimethylhexan-1,6-diamin

STOT-repeated exposure, NOAEL(C);, Rat: 10 (13 week(s))

Ingestion; liver

STOT-repeated exposure, LOAEL(C);, Rat: 60 (13 week(s))

Ingestion; liver

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Causes burns. The preparation may be a skin sensitiser. It may also be a skin irritant and repeated contact may increase this effect. Prolonged or repeated contact with skin or mucous membrane result in irritation symptoms such as redness, blistering, dermatitis, etc.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. Toxicity

benzyl alcohol

*

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 4 06789 B00V1 epple 06789-new / V1
Print date 11.05.2023 Revision date 11.05.2023
Version 7.0 11.05.2023

EN
Page 8 / 11

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 460 mg/L (96 h)

Method: EPA 600/3-76/097

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 230 mg/L (48 h)

Method: OECD 202

Daphnia toxicity, LC50, Daphnia magna (Big water flea): 360 mg/L (48 h)

Algae toxicity, EC0, Scenedesmus quadricauda: 640 mg/L (96 h)

Algae toxicity, EC50, Pseudokirchneriella subcapitata: 770 mg/L (72 h)

Method: OECD 201

Bacteria toxicity, EC10, Pseudomonas putida: 658 mg/L (16 h)

3-aminomethyl-3,5,5-trimethyl-cyclohexylamine

Fish toxicity, LC50, Leuciscus idus (golden orfe): 110 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 23 mg/L (48 h)

Daphnia toxicity, EC50: 44 mg/L (24 h)

Algae toxicity, EC50: 37 mg/L (72 h)

Bacterial toxicity, EC10, Pseudomonas putida: 1120 mg/L (18 h)

Trimethylhexan-1,6-diamin

Algae toxicity, ErC50, Pseudokirchneriella subcapitata: 43,5 mg/L (72 h)

Method: OECD 201

Bacteria toxicity, IC50, Pseudomonas putida: 89 mg/L (17 h)

Fish toxicity, LC50, Leuciscus idus (golden orfe): 174 mg/L (48 h)

Method: DIN 38412

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 31,5 mg/L (24 h)

Method: DIN 38412

Algae toxicity, EC50, Pseudokirchneriella subcapitata: 37,1 mg/L (72 h)

Method: OECD 201

Algae toxicity, NOEC, Pseudokirchneriella subcapitata: 16 mg/L (72 h)

Method: OECD 201

reaction product of m-phenylenebis(methylamine) and 4,4'-Isopropylidenediphenol, oligomeric reaction product with 1-chloro.2,3-epoxypropane

Fish toxicity, LC50: 64 mg/L (96 h)

Daphnia toxicity, EC50: 1,46 mg/L (48 h)

Algae toxicity, EC50: 30 mg/L (72 h)

Long-term Ecotoxicity

Toxic to aquatic life with long lasting effects.

Trimethylhexan-1,6-diamin

Fish toxicity, NOEC, Danio rerio (zebrafish): 10,9 mg/L (30 d)

Method: OECD 210

Daphnia toxicity, NOEC, Daphnia magna (Big water flea): 1,02 mg/L (21 d)

Method: OECD 211

Fish toxicity, LOEC, Danio rerio (zebrafish): 10,9 mg/L (30 d)

Method: OECD 210

Daphnia toxicity, LOEC, Daphnia magna (Big water flea): 1,02 mg/L (21 d)

Method: OECD 211

Toxicity to soil macroorganisms, NOEC, Eisenia fetida: >= 1000 mg/kg (56 d)

Method: OECD 222

Toxicity to soil macroorganisms, EC50, Eisenia fetida: >= 1000 mg/kg (56 d)

Method: OECD 222

12.2. Persistence and degradability

benzyl alcohol

Biodegradation: 92 - 96 % (28 d); Evaluation Readily biodegradable

Method: OECD 301C

Biodegradation: 95 - 97 % (21 d); Evaluation Readily biodegradable

Method: OECD 301A

Trimethylhexan-1,6-diamin

Biodegradation: 7 % (28 d); Evaluation Not readily biodegradable

12.3. Bioaccumulative potential

benzyl alcohol

Partition coefficient: n-octanol/water: 1,05

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 4 06789 B00V1 epple 06789-new / V1
Print date 11.05.2023 Revision date 11.05.2023
Version 7.0 11.05.2023

EN
Page 9 / 11

Trimethylhexan-1,6-diamin
Partition coefficient: n-octanol/water: 0,77

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Observe in addition any national regulations!

List of proposed waste codes/waste designations in accordance with EWC

080409* Waste adhesives and sealants containing organic solvents or other dangerous substances

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package

Dispose of packaging and contaminated filters at a official hazardous waste incinerator facility.

Recommendation:

Waste codes / waste designations according to EWC / AVV: 15 01 10*

Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1. UN number or ID number

UN 2735

14.2. UN proper shipping name

Land transport (ADR/RID):

Amines, liquid, corrosive, n.o.s.
(Trimethylhexan-1,6-diamin)

Sea transport (IMDG):

AMINES, LIQUID, CORROSIVE, N.O.S.

(Trimethylhexan-1,6-diamin, Reaktionsprodukte von m-Phenylenbis(methylamin) und 4,4'-Iso propylidendiphenol, Oligomeres Reaktionsprodukt mit 1-Chlor-2,3-Epoxypropan)

Air transport (ICAO-TI / IATA-DGR):

Amines, liquid, corrosive, n.o.s.
(Trimethylhexan-1,6-diamin)

14.3. Transport hazard class(es)

8

14.4. Packing group

III

14.5. Environmental hazards

Land transport (ADR/RID)

DANGEROUS FOR THE ENVIRONMENT

Marine pollutant

p / Reaktionsprodukte von m-Phenylenbis(methylamin) und 4,4'-Iso

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 4 06789 B00V1 epple 06789-new / V1
Print date 11.05.2023 Revision date 11.05.2023
Version 7.0 11.05.2023

EN
Page 10 / 11

Tunnel restriction code E

Sea transport (IMDG)

EmS-No. F-A, S-B

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 280

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

For professional use only. Product is not intended for consumer use.

Substance/product listed in the following inventories:

AICS no information
DSL no information
EHS no information
IECSC no information
KECI no information
MITI no information
NZLoC no information
PICCS no information
TCSI no information
TSCA no information

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
500-302-7 113930-69-1	reaction product of m-phenylenebis(methylamine) and 4,4'-Isopropylidenediphenol, oligomeric reaction product with 1-chloro-2,3-epoxypropane	01-2119965162-39
202-859-9 100-51-6	benzyl alcohol	01-2119492630-38
500-101-4 38294-64-3	Reaction products of 3-aminomethyl-3,5,5-trimethylcyclohexylamine and 4,4'-isopropylidenediphenol, oligomeric Reaction product with 1-chloro-2,3-epoxypropane	01-2119965165-33
247-134-8 25620-58-0	Trimethylhexan-1,6-diamin	01-2119560598-25
220-666-8 2855-13-2	3-aminomethyl-3,5,5-trimethyl-cyclohexylamine	01-2119514687-32
9046-10-0	Polyoxypropylen diamine	01-2119557899-12

SECTION 16: Other information

Full text of classification in section 3:

Skin Corr. 1B / H314

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 4 06789 B00V1 epple 06789-new / V1
Print date 11.05.2023 Revision date 11.05.2023
Version 7.0 11.05.2023

EN
Page 11 / 11

Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Skin Sens. 1A / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.
Skin Corr. 1C / H314	Skin corrosion/irritation	Causes severe skin burns and eye damage.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Skin Corr. 1B	Skin corrosion/irritation	Calculation method.
Eye Dam. 1	Serious eye damage/eye irritation	Calculation method.
Skin Sens. 1	Respiratory or skin sensitisation	Calculation method.
Aquatic Chronic 2	Hazardous to the aquatic environment	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Abbreviations and acronyms

n.a. = not applicable
n.b. = not determined

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version