

Article No. (manufacturer/supplier): 4 06908 A0000 Trade name/designation epple 06908 Cast resin Component A UFI: YT10-T08E-R00T-Q6C1 1.2. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses: Casting resin for casting electronic and other components. 1.3. Details of the supplier of the safety data sheet supplier (manufacturer/importer/downstream user/distributor) E. Epple & Co. GmbH Hertzstr. 8 Department responsible for information: laboratory E-mail (competent person) labor@epple-chemie.de Information center against poisoning Bonn +49 (0) 228 / 19 240 (Advice in German) SECTION 2: Hazards identification 2.1. Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 [CLP] The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Skin Irrit. 2 / H315 Skin corrosion/irritation Eye Irrit. 2 / H315 Skin corrosion/irritation Eye Irrit. 2 / H315 Skin corrosion/irritation Aquatic Chronic 2 / H411 Hazardous to the aquatic environment Toxic to aquatic life with long lasting effects.	Article Print o Versio	date 1	06908 A0000 6.05.2023 .0	epple 06908 Revision date 16 Issue date 16.05		EN Page 1 / 10
Article No. (manufacturer/supplier):       4 06908 A0000         Trade name/designation       exple 06908         Cast resin       Component A         UFL: VTI-0-T08E-R00T-Q6C1       UFL: VTI-0-T08E-R00T-Q6C1         Relevant identified uses:       Components.         Casting resin for casting electronic and other components.       Image: Casting resin for casting electronic and other components.         1.3.       Details of the supplier of the safety data sheet       Explice A for the supplier of the safety data sheet         Supplier (manufacturer/importer/downstream user/distributor)       E. Exple & Co. Ombit       Herror         Hardzary       Telephone: +49 7032 / 9771-10       www.explic-chemie.de         Details of the supplier of the substance or mixture       Cassification complier.chemie.de       Image: Casting telephone: herror         Isbordaro       Exernal (completint person)       Isbord202 / 972-000 (CLP)       Image: Casting telephone: herror         Stim Terror (Jecomponent person)       Isbord200 / 9220 / 19 240 (Advice in German)       Exercise (CLP)         Stim terror (Jecomponent person)       Isbord200 / 9220 / 19 240 (Advice in German)       Exercise (CLP)         Stim terror (Jecomponent Person)       Isbord200 / 9220 /	SEC	TION 1: Ident	tification of th	e substance/mix	ture and of the comp	any/undertaking
Trade name/designation       epple 08006 Cast resin Component A UFI; YT10-T08E-ROOT-Q6C1         12.       Relevant identified uses: Casting resin for casting electronic and other components.         13.       Details of the subplier of the safety data sheet supplier (manufacture/importar/downstream user/distributor) E. Epple & Co. GmbH Herzzir. 8 Department responsible for information: labor3002 / 9771-10 T1083 Herrenberg         Department responsible for information: labor3007 E-mail (competent person)       labor302 / 9771-10 Www.epple-chemic.de         Department responsible for information: labor3007 E-mail (competent person)       labor302 / 9771-60 Www.epple-chemic.de         SECTION 2: Hazards identification       Cassification of the substance or mixture         Classification of the substance or mixture       Causes skin initiation. Causes skin initiation. Experime (2) Hazards identification         2.1.       Classification according to Regulation (EC) No 1272/2008 [CLP] The mixture is classified as hazardous according to regulation (CC) No 1272/2008 [CLP]. The mixture is classified as hazardous according to EC directives or corresponding national laws. Labol elements         2.2.       Labol elements       *         Hazard statements       *         Hazard statements       *         Hazard statements       Causes skin initiation. Hatari tracture according to Regulation (EC) No. 1272/2008 [CLP]         Hazard pictograms       *         P2020       FO. No. Nordi b aquable for with long lasting effects. <th>1.1.</th> <th>Product iden</th> <th>tifier</th> <th></th> <th></th> <th></th>	1.1.	Product iden	tifier			
Relevant identified uses: Casting resin for casting electronic and other components.         1.3       Details of the supplier of the safety data sheet supplier (manufacturer/importer/downstream user/distributor) E. Epple & C.o. GmbH Herzstr. 8 71083 Herrenberg       Telephone: +49 7032 / 9771-17 Telefar: +49 7032 / 9771-10 www.epple-chemie.de Department responsible for information: laboratory E-mail (competent person)         1aboratory E-mail (competent person)       labor@epple-chemie.de         14.       Emergency telephone number Information center against poisoning Bonn       +49 (0) 228 / 19 240 (Advice in German)         SECTION 2: Hazardos identification       Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 [CLP]         The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Skin Irrit. 2 / H317       Skin corosion/irritation Skin Sens. 1 / H317         Skin Irrit. 2 / H319       Serious eye damage/eye irritation Skin Sens. 1 / H317       Causes serious eye irritation. May cause an allergic skin reaction. Aquatic Chronic 2 / H11         Label elements       *         The product is classified and labelled according to EC directives or corresponding national laws. Labelling according to Regulation (EC) No. 1272/2008 [CLP]         Hazard statements       *         H315       Causes skin irritation. H316         H317       May cause an allergic skin reaction. H317         H318       Causes skin irritation. H319         H319       <				plier):	epple 06908 Cast resin Component A	)T-Q6C1
Casting resin for casting electronic and other components.         1.3. Details of the supplier of the safety data sheet         supplier (manufacturer/importer/downstream user/distributor)         E. Epple & Co. GmbH         Hertzstr. 8.       Telephone: +49 7032 / 9771-17         71083 Herrenberg       Telephone: +49 7032 / 9771-60         www.epple-chemie.de       Department responsible for information:         laboratory       E-mail (competent person)         E-mail (competent person)       labor@pple-chemie.de         1.4. Emergency telephone number       Information center against poisoning Bonn         Information center against poisoning to regulation (EC) No 1272/2008 [CLP]       The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].         Skin Kinz, 1/ H315       Safu corrosion/irritation       Causes serious eye irritation.         Eye Inti. 2 / H319       Sorious eye damage/eye irritation       Causes an allergic skin reaction.         Aquatic Chronic 2 / H411       Hazardous to the aquatic environment       Toxic to aquatic life with long lasting effects.         * The product is classified and labelled according to EC directives or corresponding national laws.       Labelling according to Regulation (EC) No. 1272/2008 [CLP]         Hazard statements       *       *         H315       Causes skin irritation.         H316       Causes skin	1.2.	Relevant ider	ntified uses of	the substance or m	nixture and uses advise	ed against
supplier (manufacturer/importer/downstream user/distributor)       E: Epple & Co. SmbH         E: Epple & Co. SmbH       Telephone: +49 7032 / 9771-17         T1083 Herrenberg       Telefax: 49 7032 / 9771-80         www.epple-chemie.de          Department responsible for information:       labor@pple-chemie.de         laboratory       E-mail (competent person)       labor@pple-chemie.de         1.16.       Emergency telephone number       -         Information center against polisoning Bonn       +49 (0) 228 / 19 240 (Advice in German)         SEEULVI 2: Hazards Identification       Causes skin irritation.         Classification according to Regulation (EC) No 1272/2008 [CLP]       -         The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].       -         Skin Intri 2 / H319       Serious eye damage/eye irritation       Causes serious eye irritation.         Skin Rens 1 / H317       Respiratory or skin sensitisation       May cause an allergic skin reaction.         Aquatic Chronic 2 / H411       Hazard baleled according to EC directives or corresponding national laws.       -         Labelling according to Regulation (EC) No. 1272/2008 [CLP]       -       -         Hazard pictogram.       -       -       -         Hazard viotagram.       Causes skin irritation.       -       -     <	1.3.	Casting resin	for casting elect			
71083 Herrenberg       Telefax: +39.7032 / 9771-60 www.epple-chemile.de         Department responsible for information: laboratory       Impact the information cells of the substance or mixture         1.4.       Emergency telephone number information center against poisoning Bonn       +49 (0) 228 / 19 240 (Advice in German)         SECTION 2: Hazards identification       228 / 19 240 (Advice in German)         SECTION 2: Hazards identification       Classification according to Regulation (EC) No 1272/2008 [CLP].         Skin krint. 2 / H315       Skin corrosion/Irritation       Causes skin irritation.         Eye int. 2 / H317       Respiratory or skin sensilisation       May cause an allergic skin reaction.         Skin krint. 2 / H317       Respiratory or skin sensilisation       May cause an allergic skin reaction.         Skin Sens. 1 / H317       Respiratory or skin sensilisation       May cause an allergic skin reaction.         Aquatic Chronic 2 / H411       Hazardous to the aquatic environment       Toxic to aquatic life with long lasting effects.         2.2.       Label elements       Hazard pictograms       *         Hazard statements       Freautionage serious eye initation.       *         H315       Causes selin irritation.       *         H316       Causes selin irritation.       *         H317       May cause an allergic skin reaction.       *		supplier (mai	nufacturer/imp	-		
laboratory       E-mail (competent person)       labor@epple-chemie.de         1.4.       Emergency telephone number Information center against poisoning Bonn       +49 (0) 228 / 19 240 (Advice in German)         SECTION 2: Hazards identification         SECTION 2: Hazards identification         Classification of the substance or mixture         Classification according to Regulation (EC) No 1272/2008 [CLP]         The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].         Skin Irit. 2 / H315         Skin corrosion/irritation         Causes skin irritation.         Skin Charco (EC) No 1272/2008 [CLP].         Skin Irit. 2 / H315         Skin corrosion/irritation         Causes skin irritation.         Aquatic Chronic 2 / H411         Hazard pictograms         V         Varming         Mazard statements         Hazard statements         H315         Causes skin irritation.         H315       Causes skin irritation.         H315       Causes skin irritation.         H315       Causes skin reration. <td></td> <td>Hertzstr. 8</td> <td></td> <td></td> <td>Telefax: +49 7032 / 9</td> <td>9771-60</td>		Hertzstr. 8			Telefax: +49 7032 / 9	9771-60
E-mail (competent person)       labor@epple-chemie.de         1.4. Emergency telephone number Information center against poisoning Bonn       +49 (0) 228 / 19 240 (Advice in German)         SECTION 2: Hazards identification         SECTION 2: Hazards identification         Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 [CLP].         The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].         Skin Irrit. 2 / H315         Skin corrosion/irritation         Causes skin irritation.         Eye Irrit. 2 / H315         Skin corrosion/irritation         Causes skin irritation.         Causes skin irritation.         Again to corrosion/irritation corresponding national laws.         Label elements         The product is classified and labelled according to EC directives or corresponding national laws.         Labelling according to Regulation (EC) No. 1272/2008 [CLP]         Hazard statements         Hazard statements         Hazard statements         Hazard statements         Hazard statements         Hazard bictograms         Precautio		-	esponsible for	information:		
+49 (0) 228 / 19 240 (Advice in German)         SECTION 2: Hazards identification         Section 2: Cording to Regulation (EC) No 1272/2008 [CLP]         The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].         Skin Irrit. 2 / H315         Skin Irrit. 2 / H319         Serious eye damage/eye irritation         Causes skin irritation.         Eye Irrit. 2 / H319         Serious eye damage/eye irritation         Causes skin irritation.         Aquatic Chronic 2 / H411         Hazardous to the aquatic environment       Toxic to aquatic life with long lasting effects.         Causes skin irritation.         Aquatic Chronic 2 / H411       Hazardous to the aquatic environment       Toxic to aquatic life with long lasting effects.         Label elements       ***********************************			etent person)		labor@epple-chemie	e.de
2.1. Classification of the substance or mixture         Classification according to Regulation (EC) No 1272/2008 [CLP]         The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].         Skin Irrit. 2 / H315       Skin corrosion/irritation         Causes skin irritation.         Eye Irrit. 2 / H319       Serious eye damage/eye irritation         Gauses serious eye irritation.         Aquatic Chronic 2 / H411       Hazardous to the aquatic environment         Toxic to aquatic life with long lasting effects.         2.2. Label elements       *         The product is classified and labelled according to EC directives or corresponding national laws.         Labelling according to Regulation (EC) No. 1272/2008 [CLP]         Hazard pictograms         VV       Warning         Hazard statements         H315       Causes skin irritation.         H317       May cause an allergic skin reaction.         H319       Causes serious eye irritation.         H311       Toxic to aquatic life with long lasting effects.         Precautionary statements       P260         P280       Wear protective gloves.         P302 + P352       IF ON SKIN: Wash with plenty of soap and water.         P333 + P313       If skin initiation or rash occurs: Get medical advice/attention. <tr< td=""><td>1.4.</td><td></td><td>•</td><td></td><td>+49 (0) 228 / 19 240</td><td>(Advice in German)</td></tr<>	1.4.		•		+49 (0) 228 / 19 240	(Advice in German)
Classification according to Regulation (EC) No 1272/2008 [CLP].         Skin Irrit. 2 / H315         Skin corrosion/irritation         Causes skin irritation.         Evelocities of the application (EC) No 1272/2008 [CLP].         Skin Irrit. 2 / H315         Skin corrosion/irritation         Causes skin irritation.         Skin Serial (H317)         Respiratory or skin sensitisation         May couse an allergic skin reaction.         Aquatic Chronic 2 / H411         Hazardous to the aquatic environment         Toxic to aquatic life with long lasting effects. <b>Label elements</b> *         The product is classified and labelled according to EC directives or corresponding national laws.         Labeling according to Regulation (EC) No. 1272/2008 [CLP]         Hazard pictograms         *         Mazerd statements         Hazard statements         Hazard statements         Hazard statements         Hazard statements         Hazard statements         Procit co aquatic life with long lasting	SEC	TION 2: Haza	rds identifica	tion		
Hazard statementsH315Causes skin irritation.H319Causes serious eye irritation.H317May cause an allergic skin reaction.H411Toxic to aquatic life with long lasting effects.Precautionary statementsP261Avoid breathing vapours.P280Wear protective gloves.P302 + P352IF ON SKIN: Wash with plenty of soap and water.P333 + P313If skin irritation or rash occurs: Get medical advice/attention.P362 + P364Take off contaminated clothing and wash it before reuse.P501Dispose of contents / container to a certified waste management company.Hazard components for labelling Methyl toluene-4-sulfonate 1,6-hexanediol diglycidyl etherSupplemental hazard information	2.2.	Skin Irrit. 2 / H Eye Irrit. 2 / H Skin Sens. 1 / Aquatic Chror Label elemen The product is Labelling acc	I315 319 H317 hic 2 / H411 h <b>ts</b> classified and cording to Regi	Skin corrosion/irri Serious eye dama Respiratory or ski Hazardous to the	tation age/eye irritation n sensitisation aquatic environment o EC directives or corres	Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.
H315Causes skin irritation.H319Causes serious eye irritation.H317May cause an allergic skin reaction.H411Toxic to aquatic life with long lasting effects.Precautionary state===================================				Warning		
1,6-hexanediol diglycidyl ether Supplemental hazard information		H315 H319 H317 H411 <b>Precautionar</b> P261 P280 P302 + P352 P333 + P313 P362 + P364 P501	Causes Causes May ca Toxic to y statements Avoid b Wear p IF ON If skin i Take o Dispos ponents for labo bis-[4-(	s serious eye irritation iuse an allergic skin o aquatic life with lor preathing vapours. protective gloves. SKIN: Wash with ple rritation or rash occu ff contaminated clott e of contents / conta elling 2,3-epoxipropoxi)ph	reaction. ng lasting effects. enty of soap and water. urs: Get medical advice/a hing and wash it before r ainer to a certified waste	reuse.
		Cupalars			ther	
					ts. May produce an allerg	gic reaction.



Article No.:	4 06908 A0000	epple 06908
Print date	16.05.2023	Revision date 16.05.2023
Version	9.0	Issue date 16.05.2023

## 2.3. Other hazards

No information available.

# SECTION 3: Composition/information on ingredients 3.2. Mixtures Description Epoxy resin based on bisphenol A Hazardous ingredients Classification according to Regulation (EC) No 1272/2008 [CLP] EC No. REACH No. CAS No. Designation Index No. classification: // Remark 216.823.5 01.2110456610.26

216-823-5	01-2119456619-26	
1675-54-3	bis-[4-(2,3-epoxipropoxi)phenyl]propane	74,9 - 100
603-073-00-2	Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Aquatic Chronic	
	2 H411	
	Specific concentration limit (SCL): Eye Irrit. 2 H319 >= 5 / Skin Irrit. 2 H315 >= 5	
240-260-4	01-2119463471-41	
16096-31-4	1,6-hexanediol diglycidyl ether	9,9 - 19,9
	Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Aquatic Chronic 3 H412	
201-283-5	01-2120211468-59	
80-48-8	Methyl toluene-4-sulfonate	0,1 - 0,9
	Acute Tox. 4 H302 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1	
	H317 / STOT SE 3 H335	
	Acute toxicity estimate (ATE): ATE (oral): 341 mg/kg bw	

# Additional information

Full text of classification: see section 16

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

## **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

## In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

## Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

# After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

## **Following ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

## 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

# 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

# SECTION 5: Firefighting measures

# 5.1. Extinguishing media

Suitable extinguishing media alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)



Article No.:	4 06908 A0000	epple 06908
Print date	16.05.2023	Revision date 16.05.2023
Version	9.0	Issue date 16.05.2023

#### Unsuitable extinguishing media

strong water jet

## 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

## 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

## 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

# 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

## Advices on safe handling

Avoid contact with skin, eyes and clothes. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Follow the legal protection and safety regulations.

## 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

# Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

#### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

## 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

# SECTION 8: Exposure controls/personal protection

# 8.1. Control parameters

# Occupational exposure limit values

not applicable

# DNEL:

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Index No. 603-073-00-2 / EC No. 216-823-5 / CAS No. 1675-54-3 DNEL acute dermal, short-term (systemic), Workers: 8,3 mg/kg bw/day DNEL long-term dermal (systemic), Workers: 8,3 mg/kg bw/day

DNEL acute inhalative (systemic), Workers: 12,3 mg/m<sup>3</sup>

DNEL long-term inhalative (systemic), Workers: 12,3 mg/m<sup>3</sup>

1,6-hexanediol diglycidyl ether

EC No. 240-260-4 / CAS No. 16096-31-4

DNEL acute dermal, short-term (local), Workers: 0,0226 mg/cm<sup>2</sup>



Article No.: 4 06908 A0000 Print date 16.05.2023 epple 06908 Revision date 16.05.2023 Issue date 16.05.2023 DNEL long-term dermal (systemic), Workers: 2,8 mg/kg bw/day DNEL long-term inhalative (systemic), Workers: 0,44 mg/m<sup>3</sup> PNEC: bis-[4-(2,3-epoxipropoxi)phenyl]propane

Index No. 603-073-00-2 / EC No. 216-823-5 / CAS No. 1675-54-3

PNEC aquatic. freshwater: 6 µg/L

PNEC aquatic, marine water: 1 µg/L

PNEC aquatic, intermittent release: 0,013 mg/L

PNEC sediment, freshwater: 0,996 mg/kg dw

PNEC sediment, marine water: 0,1 mg/kg dw

PNEC, soil: 0,196 mg/kg dw

PNEC sewage treatment plant (STP): 10 mg/L

1,6-hexanediol diglycidyl ether

EC No. 240-260-4 / CAS No. 16096-31-4 PNEC aquatic, freshwater: 0,0115 mg/L PNEC aquatic, marine water: 0,0011 mg/L PNEC aquatic, intermittent release: 0,115 mg/L PNEC sediment, freshwater: 0,283 mg/kg PNEC sediment, marine water: 0,0283 mg/kg PNEC, soil: 0,223 mg/kg PNEC sewage treatment plant (STP): 1 mg/L

# 8.2. Exposure controls

# Personal protection equipment

# **Respiratory protection**

If the workplace limit values (AGW) are exceeded, a suitable breathing apparatus must be worn. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Use filter / combination filter according to EN 14387.

Suitable respiratory protection apparatus: ABEK-P2

# Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

# Eye/face protection

Wear eye glasses with side protection according to EN 166.

# Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

# Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: Appearance: Colour:	Liquid Liquid translucent
Odour:	characteristic
Odour threshold:	not applicable
Melting point/freezing point	<b>8 °C</b> Source: bis-[4-(2,3-epoxipropoxi)phenyl]propane
Initial boiling point and boiling range:	not applicable
Flammability:	Combustible liquid.
Lower and upper explosion limit:	



Article Print c Versic	late	4 06908 A0000 16.05.2023 9.0	epple 06908 Revision date 1 Issue date 16.0		EN Page 5 / 10
	Upper e Flash poi Auto-igni	xplosion limit: xplosion limit: nt: tion temperature: sition temperature:		not applicable not applicable 149 °C not applicable not applicable	
	pH at 20 °	-		not relevant	
	Cinematio	c viscosity (40°C):		2586,21 mm²/s	
	Viscosity	at 20 °C:		2 - 4 Pa*s	
	Solubility Water so	(ies): lubility at 20 °C:		insoluble	
	Partition	coefficient: n-octan	ol/water:	see section 12	
	Vapour p	ressure at 20 °C:		not applicable	
	Density a Density a	nd/or relative densi at 20 °C:	ty:	1,16 g/cm³	
	-	apour density:		not applicable	
	particle c	haracteristics:		not applicable	
9.2.	Other info	ormation			
	Solvent s	eparation test:		< 3 weight-% (A	ADR/RID)
SEC	TION 10: 3	Stability and react	tivity		
10.1.	Reactivity	<b>/</b> ation available.			
10.2.	<b>Chemical</b> Stable wh section 7.	-	mmended regulat	ions for storage a	and handling. Further information on correct storage: refer to
10.3.		<b>y of hazardous reac</b> y from strong acids, s		strong oxidizing a	agents to avoid exothermic reactions.
10.4.		<b>is to avoid</b> s decomposition bypi	roducts may form	with exposure to	high temperatures.
10.5.	Incompation Incompation	<b>ible materials</b> able			
10.6.	Hazardou	is decomposition pi s decomposition byp trogen oxides.		with exposure to	high temperatures, e.g.: carbon dioxide, carbon monoxide,
SEC	TION 11:	Toxicological info	rmation		
11.1.	Information	on on hazard classe	es as defined in I	Regulation (EC)	No 1272/2008 *
	Acute tox	icity			
	oral, LDS dermal, I Method:	-epoxipropoxi)pheny 50, Rat: > 2000 mg/kg LD50, Rat: > 2000 mg OECD 402 LD50, Rabbit: > 2000	g g/kg		
		uene-4-sulfonate 50, Rat: 341 mg/kg			
	1 6-hevan	ediol dialycidyl ether			

1,6-hexanediol diglycidyl ether oral, LD50, Rat: 3741 mg/kg dermal, LD50, Rat: > 2000 mg/kg inhalative (vapours), LC50, Rat: > 0,035 mg/L (4 h)

# Skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye irritation.



Article No.:	4 06908 A0000	epple 06908
Print date	16.05.2023	Revision date 16.05.2023
Version	9.0	Issue date 16.05.2023

Methyl toluene-4-sulfonate Skin, Rabbit (24 h): Evaluation strongly irritant. eyes, Rabbit (24 h): Evaluation mild irritant.

#### Respiratory or skin sensitisation

May cause an allergic skin reaction.

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

## STOT-single exposure; STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

## Practical experience/human evidence

Based on the properties of the epoxy constituents and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and an irritant. It contains low molecular weight epoxy constituents which are irritating to eyes, mucous membrane and skin. Repeated skin contact may result in irritations and sensitizations, possibly due to a cross-over sensitization with other epoxy compounds. Skin contact with the preparation and exposure to spray mist and vapour should be avoided.

## **Overall assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP. **Remark** 

There is no information available on the preparation itself .

#### 11.2. Information on other hazards

## **Endocrine disrupting properties** No information available.

## **SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

Partition coefficient: n-octanol/water: Mixtures: Not applicable.Do not allow to enter into surface water or drains.

## 12.1. Toxicity

bis-[4-(2,3-epoxipropoxi)phenyl]propane Fish toxicity, LC50: 1,3 mg/L (96 h) Method: OECD 203 Daphnia toxicity, EC50: 2,1 mg/L (48 h) Method: OECD 202

1,6-hexanediol diglycidyl ether Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): 30 mg/L (96 h) Daphnia toxicity, EC50, Daphnia magna (Big water flea): 47 mg/L (48 h)

# Long-term Ecotoxicity

Toxic to aquatic life with long lasting effects.

bis-[4-(2,3-epoxipropoxi)phenyl]propane Daphnia toxicity, NOEC: 0,3 mg/L (21 d) Method: OECD 211

## 12.2. Persistence and degradability

There are no data available on the preparation/mixture itself.

bis-[4-(2,3-epoxipropoxi)phenyl]propane
Biodegradation:: 5 % (28 d); Evaluation Not readily biodegradable (according to OECD criteria)
Method: OECD 301F
Biodegradation:: 6 - 12 % (28 d); Evaluation Not readily biodegradable (according to OECD criteria)
Method: OECD 301B

1,6-hexanediol diglycidyl ether

: 47 % (28 d); Evaluation Not readily biodegradable (according to OECD criteria) Method: OECD 301D



Article No.:	4 06908 A0000	epple 06908
Print date	16.05.2023	Revision date 16.05.2023
Version	9.0	Issue date 16.05.2023

## 12.3. Bioaccumulative potential

bis-[4-(2,3-epoxipropoxi)phenyl]propane Partition coefficient: n-octanol/water: 2,64 - 3,78

1,6-hexanediol diglycidyl ether Partition coefficient: n-octanol/water: 0,822 Method: OECD 107

# **Bioconcentration factor (BCF)**

bis-[4-(2,3-epoxipropoxi)phenyl]propane Bioconcentration factor (BCF): 3 - 31

1,6-hexanediol diglycidyl ether Bioconcentration factor (BCF): < 100

## 12.4. Mobility in soil

Toxicological data are not available.

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

- 12.6. **Endocrine disrupting properties** No information available.
- 12.7. Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

# Appropriate disposal / Product

## Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Observe in addition any national regulations!

## List of proposed waste codes/waste designations in accordance with EWC

080409\* Waste adhesives and sealants containing organic solvents or other dangerous substances \*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

# Appropriate disposal / Package

**Dispose of packaging and contaminated filters at a offical hazardous waste incinerator facility.** Recommendation: Waste codes / waste designations according to EWC / AVV: 15 01 10\*

Non-contaminated packages may be recycled.

# **SECTION 14: Transport information**

14.1.	UN number or ID number	
		UN 3082
14.2.	UN proper shipping name	
	Land transport (ADR/RID):	Environmentally hazardous substance, liquid, n.o.s. (4,4'-methylene diphenyl diglycidyl ether)
	Sea transport (IMDG):	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4,4'-methylene diphenyl diglycidyl ether)
	Air transport (ICAO-TI / IATA-DGR):	Environmentally hazardous substance, liquid, n.o.s. (4,4'-methylene diphenyl diglycidyl ether)
14.3.	Transport hazard class(es)	
		9
14.4.	Packing group	
		III
14.5.	Environmental hazards	
	Land transport (ADR/RID)	DANGEROUS FOR THE ENVIRONMENT
	Marine pollutant	p / 4,4'-methylene diphenyl diglycidyl ether



Article No.:	4 06908 A0000	epple 06908
Print date	16.05.2023	Revision date 16.05.2023
Version	9.0	Issue date 16.05.2023

#### 14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

# **Further information**

## Land transport (ADR/RID)

Tunnel restriction code

in packages <= 5 litres

**KEIN GUT DER KLASSE 9** 

#### Sea transport (IMDG)

EmS-No.

in packages <= 5 litres

F-A, S-F NOT RESTRICTED 2.10.2.7

# Air transport (ICAO-TI / IATA-DGR)

in packages <= 5 litres

NOT RESTRICTED

## 14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive] VOC-value (in g/L): 0

## National regulations

## **Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

For professional use only. Product is not intended for consumer use.

## Substance/product listed in the following inventories:

AICS listed DSL listed EHS no information IECSC listed KECI listed MITI listed NZLoC no information PICCS listed TCSI no information TSCA listet

## 15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No.	Designation	REACH No.
CAS No.		
216-823-5	bis-[4-(2,3-epoxipropoxi)phenyl]propane	01-2119456619-26
1675-54-3		
240-260-4	1,6-hexanediol diglycidyl ether	01-2119463471-41
16096-31-4		



 Article No.:
 4 06908 A0000
 epple 06908

 Print date
 16.05.2023
 Revision date 16.05.2023

 Version
 9.0
 Issue date 16.05.2023

Methyl toluene-4-sulfonate

EN Page 9 / 10

01-2120211468-59

201-283-5 80-48-8

**SECTION 16: Other information** 

Full text of classification in section 3: Skin Irrit. 2 / H315 Skin corrosion/irritation Causes skin irritation. Eve Irrit. 2 / H319 Serious eye damage/eye irritation Causes serious eye irritation. Skin Sens. 1 / H317 Respiratory or skin sensitisation May cause an allergic skin reaction. Aquatic Chronic 2 / H411 Hazardous to the aquatic environment Toxic to aquatic life with long lasting effects. Aquatic Chronic 3 / H412 Hazardous to the aquatic environment Harmful to aquatic life with long lasting effects. Acute Tox. 4 / H302 Acute toxicity (oral) Harmful if swallowed. STOT SE 3 / H335 STOT-single exposure May cause respiratory irritation. **Classification procedure** Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP] Skin corrosion/irritation Calculation method. Skin Irrit. 2 Eye Irrit. 2 Serious eye damage/eye irritation Calculation method. Skin Sens. 1 Respiratory or skin sensitisation Calculation method. Hazardous to the aquatic environment Aquatic Chronic 2 Calculation method. Abbreviations and acronyms ADR European Agreement concerning the International Carriage of Dangerous Goods by Road OEL Occupational Exposure Limit Value BLV **Biological Limit Value** CAS **Chemical Abstracts Service** CLP Classification, Labelling and Packaging Carcinogenic, Mutagenic and Reprotoxic CMR DIN German Institute for Standardization / German industrial standard DNEL Derived No-Effect Level European Waste Catalogue Directive EAKV Effective Concentration EC EC European Community ΕN European Standard IATA-DGR International Air Transport Association – Dangerous Goods Regulations IBC Code International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk ICAO-TI International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air IMDG Code International Maritime Code for Dangerous Goods ISO International Organization for Standardization LC Lethal Concentration LD Lethal Dose MARPOL Maritime Pollution: The International Convention for the Prevention of Pollution from Ships OECD Organisation for Economic Cooperation and Development persistent, bioaccumulative, toxic PBT PNEC Predicted No Effect Concentration REACH Registration, Evaluation, Authorisation and Restriction of Chemicals RID Regulations concerning the International Carriage of Dangerous Goods by Rail UN United Nations VOC Volatile Organic Compounds vPvB very persistent and very bioaccumulative Abbreviations and acronyms n.a. = not applicable

n.b. = not determined

## **Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

\* Data changed compared with the previous version



 Article No.:
 4 06908 A0000
 epple 06908

 Print date
 16.05.2023
 Revision date 16.05.2023

 Version
 9.0
 Issue date 16.05.2023

EN Page 10 / 10