# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 6 00020 00000 epple dilution 456
Print date 13.04.2023 Revision date 13.04.2023
Version 8.0 13.04.2023





# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Article No. (manufacturer/supplier): 6 00020 00000
Trade name/designation epple dilution 456

UFI: C9D0-J0FV-4005-EUEW

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses:

Product for cleaning or diluting sealants or adhesives.

### 1.3. Details of the supplier of the safety data sheet

# supplier (manufacturer/importer/downstream user/distributor)

E. Epple & Co. GmbH

Hertzstr. 8 Telephone: +49 7032 / 9771-17 71083 Herrenberg Telefax: +49 7032 / 9771-60 www.epple-chemie.de

### **Department responsible for information:**

laboratory

E-mail (competent person) labor@epple-chemie.de

1.4. Emergency telephone number

Information center against poisoning Bonn +49 (0) 228 / 19 240 (Advice in German)

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

# Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2 / H225 Flammable liquids Highly flammable liquid and vapour.

Skin Irrit. 2 / H315 Skin corrosion/irritation Causes skin irritation.

Repr. 2 / H361 Reproductive toxicity Suspected of damaging fertility or the unborn

child.

STOT SE 3 / H336 STOT-single exposure May cause drowsiness or dizziness.
STOT RE 2 / H373 STOT-repeated exposure May cause damage to organs through

prolonged or repeated exposure.

Asp. Tox. 1 / H304 Aspiration hazard May be fatal if swallowed and enters airways. Aquatic Chronic 2 / H411 Hazardous to the aquatic environment Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

# Labelling according to Regulation (EC) No. 1272/2008 [CLP]

### Hazard pictograms









**Danger** 

### **Hazard statements**

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

### **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapour.
P280 Wear protective gloves.
P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: Print date Version 6 00020 00000 13.04.2023 epple dilution 456

Revision date 13.04.2023

8.0 13.04.2023



EN Page 2 / 8

Hazard components for labelling

hydrocarbons, C6, n-alkanes, isoalkanes, cyclics, n-hexane rich

Dispose of contents / container to a certified waste management company.

nydrocarbon

Supplemental hazard information not applicable

2.3. Other hazards

P501

No information available.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

**Description** Solvents/Thinner

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No.	REACH No.	
CAS No.	Designation	weight-%
Index No.	classification: // Remark	<u> </u>
925-292-5	01-2119474209-33	
92112-69-1	hydrocarbons, C6, n-alkanes, isoalkanes, cyclics, n-hexane rich	74,9 - 100
649-328-00-1	Flam. Liq. 2 H225 / Skin Irrit. 2 H315 / Repr. 2 H361 / Asp. Tox. 1 H304 /	
	STOT RE 2 H373 / STOT SE 3 H336 / Aquatic Chronic 2 H411	

### Additional information

Full text of classification: see section 16

### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

### Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

# **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

### Unsuitable extinguishing media

strong water jet

# 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

# 5.3. Advice for firefighters

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: Print date Version 6 00020 00000 13.04.2023 epple dilution 456 Revision date 13.04.2023

13.04.2023

EN Page 3 / 8



Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

### 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

#### 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

# **Further information**

Vapours are heavier than air. Vapours form explosive mixtures with air.

# 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Floors must be electrically conductive.

### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

# SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

# Occupational exposure limit values

not applicable

# 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

# Personal protection equipment

# Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 6 00020 00000 epple dilution 456 Print date 13.04.2023 Revision date 13.04.2023 Version

13.04.2023



ΕN Page 4 / 8

apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Use combination filters according to EN 14387. Suitable respiratory protection apparatus: ABEK-P2

### Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0.4 mm; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

### Eye/face protection

Wear eye glasses with side protection according to EN 166.

### **Body protection**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

#### **Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

### **Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: Liquid Appearance: Liquid translucent Colour: Odour: characteristic not applicable **Odour threshold:** Melting point/freezing point: < -20 °C Initial boiling point and boiling range:

Highly flammable liquid and vapour. Flammability:

Lower and upper explosion limit:

1.2 Vol-% Lower explosion limit: Upper explosion limit: 8.3 Vol-% -25 °C Flash point: Auto-ignition temperature: > 200 °C **Decomposition temperature:** not applicable pH at 20 °C: not relevant Cinematic viscosity (40°C): < 20 mm<sup>2</sup>/s

Viscosity at 20 °C: 10 s 4 mm

Method: DIN 53211

Solubility(ies):

insoluble Water solubility at 20 °C: Partition coefficient: n-octanol/water: see section 12 Vapour pressure at 20 °C: 320 mbar

Density and/or relative density:

Density at 20 °C: 0,67 g/cm<sup>3</sup> Relative vapour density: not applicable particle characteristics: not applicable

9.2. Other information

# **SECTION 10: Stability and reactivity**

10.1. Reactivity

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: Print date Version 6 00020 00000 13.04.2023

epple dilution 456 Revision date 13.04.2023

13.04.2023

EN Page 5 / 8



No information available.

### 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

## 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

### 10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

### 10.5. Incompatible materials

not applicable

## 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Based on available data, the classification criteria are not met.

# Skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

# Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Suspected of damaging fertility or the unborn child.

### STOT-single exposure; STOT-repeated exposure

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

### **Aspiration hazard**

May be fatal if swallowed and enters airways.

# Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

### Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

# Remark

There is no information available on the preparation itself.

# 11.2. Information on other hazards

### **Endocrine disrupting properties**

No information available.

### **SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

### 12.1. Toxicity

Based on available data, the classification criteria are not met.

# Long-term Ecotoxicity

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

6 00020 00000 Article No.: epple dilution 456 Print date 13.04.2023 Revision date 13.04.2023 Version

13.04.2023



ΕN Page 6 / 8

Toxic to aquatic life with long lasting effects.

# 12.2. Persistence and degradability

Toxicological data are not available.

### 12.3. Bioaccumulative potential

Toxicological data are not available.

# 12.4. Mobility in soil

Toxicological data are not available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

No information available.

#### 12.7. Other adverse effects

No information available.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

### Appropriate disposal / Product

### Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Observe in addition any national regulations!

### List of proposed waste codes/waste designations in accordance with EWC

140603\* other solvents and solvent mixtures

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

## Appropriate disposal / Package

Dispose of packaging and contaminated filters at a offical hazardous waste incinerator facility.

Recommendation:

Waste codes / waste designations according to EWC / AVV: 15 01 10\*

Non-contaminated packages may be recycled.

# **SECTION 14: Transport information**

### 14.1. UN number or ID number

UN 1208

14.2. UN proper shipping name

Land transport (ADR/RID): Hexanes Sea transport (IMDG): **HEXANES** Air transport (ICAO-TI / IATA-DGR): Hexanes

14.3. Transport hazard class(es)

3

14.4. Packing group

Ш

14.5. Environmental hazards

Land transport (ADR/RID) DANGEROUS FOR THE ENVIRONMENT

Marine pollutant р

### 14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

# **Further information**

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: Print date Version 6 00020 00000 13.04.2023 epple dilution 456 Revision date 13.04.2023

13.04.2023

EN Page 7 / 8



Land transport (ADR/RID)

Tunnel restriction code

D/E

Sea transport (IMDG)

EmS-No. F-E, S-D

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** legislation

# Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 675

### **National regulations**

#### **Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

### Further details:

For professional use only. Product is not intended for consumer use.

### Substance/product listed in the following inventories:

AICS no informtion

DSI listed

EHS no information

IECSC no information

**KECI** listed

MITI no information

NZLoC no information

PICCS listed

TCSI no information

TSCA listet

### 15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No.	Designation	REACH No.	
CAS No.			
925-292-5	hydrocarbons, C6, n-alkanes, isoalkanes, cyclics, n-hexane rich	01-2119474209-33	
92112-69-1			

# **SECTION 16: Other information**

Full text of classification in section 3

Flam. Liq. 2 / H225 Flammable liquids
Skin Irrit. 2 / H315 Skin corrosion/irritation

Repr. 2 / H361 Reproductive toxicity

Asp. Tox. 1 / H304 Aspiration hazard

STOT RE 2 / H373 STOT-repeated exposure

Highly flammable liquid and vapour.

Causes skin irritation.

Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard). May be fatal if swallowed and enters airways. May cause damage to organs (or state all organs affected, if known) through prolonged or

repeated exposure (state route of exposure if it is conclusively proven that no other routes of

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

6 00020 00000 epple dilution 456 Article No.: Print date 13.04.2023 Revision date 13.04.2023 Version 13.04.2023



ΕN Page 8 / 8

exposure cause the hazard). STOT SE 3 / H336 STOT-single exposure May cause drowsiness or dizziness.

Aquatic Chronic 2 / H411 Hazardous to the aquatic environment Toxic to aquatic life with long lasting effects.

### Abbreviations and acronyms

European Agreement concerning the International Carriage of Dangerous Goods by Road ADR

OEL Occupational Exposure Limit Value

BLV Biological Limit Value CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging **CMR** Carcinogenic, Mutagenic and Reprotoxic

German Institute for Standardization / German industrial standard DIN

Derived No-Effect Level **DNEL** 

European Waste Catalogue Directive **EAKV** 

FC Effective Concentration **European Community** EC European Standard FΝ

IATA-DGR International Air Transport Association – Dangerous Goods Regulations

IBC Code International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk ICAO-TI International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous

Goods by Air

IMDG Code International Maritime Code for Dangerous Goods ISO International Organization for Standardization

LC Lethal Concentration

LD Lethal Dose

**MARPOL** Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

Organisation for Economic Cooperation and Development OFCD

persistent, bioaccumulative, toxic PRT **PNEC** Predicted No Effect Concentration

Registration, Evaluation, Authorisation and Restriction of Chemicals REACH

RID Regulations concerning the International Carriage of Dangerous Goods by Rail

UN **United Nations** 

VOC Volatile Organic Compounds

very persistent and very bioaccumulative vPvB

# **Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

<sup>\*</sup> Data changed compared with the previous version