

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 6 00021 00000 epple Dilution 477
Print date 09.05.2023 Revision date 09.05.2023
Version 8.0 09.05.2023

EN
Page 1 / 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier): 6 00021 00000
Trade name/designation epple Dilution 477
UFI: WH80-903D-N00D-ATT2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Product for cleaning or diluting sealants or adhesives.

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

E. Epple & Co. GmbH

Hertzstr. 8

71083 Herrenberg

Telephone: +49 7032 / 9771-17

Telefax: +49 7032 / 9771-60

www.epple-chemie.de

Department responsible for information:

laboratory

E-mail (competent person)

labor@epple-chemie.de

1.4. Emergency telephone number

Information center against poisoning Bonn

+49 (0) 228 / 19 240 (Advice in German)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

*

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2 / H225

Flammable liquids

Highly flammable liquid and vapour.

Skin Irrit. 2 / H315

Skin corrosion/irritation

Causes skin irritation.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

STOT SE 3 / H336

STOT-single exposure

May cause drowsiness or dizziness.

Asp. Tox. 1 / H304

Aspiration hazard

May be fatal if swallowed and enters airways.

Aquatic Chronic 2 / H411

Hazardous to the aquatic environment

Toxic to aquatic life with long lasting effects.

2.2. Label elements

*

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H225

Highly flammable liquid and vapour.

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

H304

May be fatal if swallowed and enters airways.

H411

Toxic to aquatic life with long lasting effects.

Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P273

Avoid release to the environment.

P280

Wear protective gloves.

P301 + P310

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P332 + P313

If skin irritation occurs: Get medical advice/attention.

P501

Dispose of contents / container to a certified waste management company.

Hazard components for labelling

Ethyl acetate

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

Supplemental hazard information

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 6 00021 00000 epple Dilution 477
 Print date 09.05.2023 Revision date 09.05.2023
 Version 8.0 09.05.2023

EN
 Page 2 / 13

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures *

Description Solvents/Thinner

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No. Designation classification: // Remark	weight-%
205-500-4 141-78-6	01-2119475103-46 Ethyl acetate	19,9 - 24,9
607-022-00-5	Eye Irrit. 2 H319 / STOT SE 3 H336 / Flam. Liq. 2 H225 / EUH066	
200-662-2 67-64-1	01-2119471330-49 Acetone	19,9 - 24,9
606-001-00-8	Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336 / EUH066	
926-605-8	01-2119486291-36 Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2 H225 / Asp. Tox. 1 H304 / STOT SE 3 H336 / Aquatic Chronic 2 H411	9,9 - 19,9
921-024-6	01-2119475514-35 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2 H225 / Skin Irrit. 2 H315 / Asp. Tox. 1 H304 / STOT SE 3 H336 / Aquatic Chronic 2 H411	9,9 - 19,9
927-510-4	01-2119475515-33 Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Skin Irrit. 2 H315 / STOT SE 3 H336 / Asp. Tox. 1 H304 / Aquatic Chronic 2 H411 / Flam. Liq. 2 H225	9,9 - 19,9
931-254-9	01-2119484651-34 Hydrocarbons, C6, isoalkanes, <5% n-hexane Flam. Liq. 2 H225 / Skin Irrit. 2 H315 / Asp. Tox. 1 H304 / STOT SE 3 H336 / Aquatic Chronic 2 H411	2,4 - 9,9
201-159-0 78-93-3	01-2119457290-43 butanone	2,4 - 9,9
606-002-00-3	Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336 / EUH066	
203-777-6 110-54-3	01-2119480412-44 n-Hexane	0,9 - 2,4
601-037-00-0	Flam. Liq. 2 H225 / Repr. 2 H361 / Asp. Tox. 1 H304 / STOT RE 2 H373 / Skin Irrit. 2 H315 / STOT SE 3 H336 / Aquatic Chronic 2 H411 Specific concentration limit (SCL): STOT RE 2 H373 >= 5	
203-806-2 110-82-7	01-2119463273-41 cyclohexane	0,1 - 0,9
601-017-00-1	Flam. Liq. 2 H225 / Asp. Tox. 1 H304 / Skin Irrit. 2 H315 / STOT SE 3 H336 / Aquatic Acute 1 H400 / Aquatic Chronic 1 H410	

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 6 00021 00000 epple Dilution 477
Print date 09.05.2023 Revision date 09.05.2023
Version 8.0 09.05.2023

EN
Page 4 / 13

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Floors must be electrically conductive.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

Ethyl acetate

Index No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

TWA: 730 mg/m³; 200 ppm

STEL: 1460 mg/m³; 400 ppm

Acetone

Index No. 606-001-00-8 / EC No. 200-662-2 / CAS No. 67-64-1

TWA: 1810 mg/m³; 750 ppm

STEL: 3620 mg/m³; 1500 ppm

Hydrocarbons, C₆, isoalkanes, <5% n-hexane

EC No. 931-254-9

TWA: 1800 mg/m³; 500 ppm

butanone

Index No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

TWA: 600 mg/m³; 200 ppm

STEL: 899 mg/m³; 300 ppm

n-Hexane

Index No. 601-037-00-0 / EC No. 203-777-6 / CAS No. 110-54-3

TWA: 72 mg/m³; 20 ppm

cyclohexane

Index No. 601-017-00-1 / EC No. 203-806-2 / CAS No. 110-82-7

TWA: 350 mg/m³; 100 ppm

STEL: 1050 mg/m³; 300 ppm

Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

butanone

Index No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

DNEL long-term dermal (systemic), Workers: 1161 mg/kg

DNEL long-term inhalative (systemic), Workers: 600 mg/m³

DNEL long-term oral (repeated), Consumer: 31 mg/kg

DNEL acute dermal, short-term (local), Consumer: 412 mg/kg

DNEL long-term inhalative (systemic), Consumer: 106 mg/m³

Ethyl acetate

Index No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

DNEL short-term oral (acute), Workers:

DNEL long-term dermal (systemic), Workers: 63 mg/kg bw/day

DNEL acute inhalative (local), Workers: 1468 mg/m³

DNEL acute inhalative (systemic), Workers: 1468 mg/m³

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 6 00021 00000 epple Dilution 477
Print date 09.05.2023 Revision date 09.05.2023
Version 8.0 09.05.2023

EN
Page 5 / 13

DNEL long-term inhalative (local), Workers: 734 mg/m³
DNEL long-term inhalative (systemic), Workers: 734 mg/m³
DNEL short-term oral (acute), Consumer:
DNEL long-term dermal (systemic), Consumer: 37 mg/kg bw/day

Acetone

Index No. 606-001-00-8 / EC No. 200-662-2 / CAS No. 67-64-1
DNEL long-term dermal (systemic), Workers: 186 mg/kg bw/day
DNEL acute inhalative (local), Workers: 2420 mg/m³
DNEL long-term inhalative (systemic), Workers: 1210 mg/m³

cyclohexane

Index No. 601-017-00-1 / EC No. 203-806-2 / CAS No. 110-82-7
DNEL long-term dermal (systemic), Workers: 2016 mg/kg bw/day
DNEL acute inhalative (local), Workers: 700 mg/m³
DNEL acute inhalative (systemic), Workers: 700 mg/m³
DNEL long-term inhalative (systemic), Workers: 700 mg/m³

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

EC No. 926-605-8
DNEL long-term dermal (systemic), Workers: 13964 mg/kg
DNEL long-term inhalative (systemic), Workers: 5306 mg/m³

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

EC No. 921-024-6
DNEL long-term dermal (systemic), Workers: 733 mg/kg
DNEL long-term inhalative (systemic), Workers: 2035 mg/m³

Hydrocarbons, C6, isoalkanes, <5% n-hexane

EC No. 931-254-9
DNEL long-term dermal (systemic), Workers: 13964 mg/kg
DNEL long-term inhalative (systemic), Workers: 5306 mg/m³

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

EC No. 927-510-4
DNEL long-term dermal (systemic), Workers: 300 mg/kg
DNEL long-term inhalative (systemic), Workers: 2085 mg/m³

PNEC:

butanone

Index No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3
PNEC aquatic, freshwater: 55,8 mg/L
PNEC aquatic, marine water: 55,8 mg/L
PNEC aquatic, intermittent release: 55,8 mg/L
PNEC sediment, freshwater: 284,7 mg/kg
PNEC sediment, marine water: 284,7 mg/kg
PNEC, soil: 22,5 mg/kg

Ethyl acetate

Index No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6
PNEC aquatic, freshwater: 0,26 mg/L
PNEC aquatic, marine water: 0,026 mg/L
PNEC aquatic, intermittent release: 1,65 mg/L
PNEC sediment, freshwater: 1,25 mg/kg
PNEC sediment, marine water: 0,125 mg/kg
PNEC, soil: 0,24 mg/kg
PNEC sewage treatment plant (STP): 650 mg/L

Acetone

Index No. 606-001-00-8 / EC No. 200-662-2 / CAS No. 67-64-1
PNEC aquatic, freshwater: 10,6 mg/L
PNEC aquatic, marine water: 1,06 mg/L
PNEC aquatic, intermittent release: 21 mg/L
PNEC sediment, freshwater: 30,4 mg/kg
PNEC sediment, marine water: 3,04 mg/kg
PNEC, soil: 29,5 mg/kg

cyclohexane

Index No. 601-017-00-1 / EC No. 203-806-2 / CAS No. 110-82-7

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 6 00021 00000 epple Dilution 477
Print date 09.05.2023 Revision date 09.05.2023
Version 8.0 09.05.2023

EN
Page 6 / 13

PNEC aquatic, freshwater: 0,207 mg/L
PNEC aquatic, marine water: 0,207 mg/L
PNEC aquatic, intermittent release: 0,207 mg/L
PNEC, soil: 2,99 mg/kg
PNEC sewage treatment plant (STP): 3,24 mg/L

8.2. **Exposure controls** *

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Use filter / combination filter according to EN 14387.

Suitable respiratory protection apparatus: Gas filter type A

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear eye glasses with side protection according to EN 166.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. **Information on basic physical and chemical properties** *

Physical state:	Liquid
Appearance:	Liquid
Colour:	translucent
Odour:	like Solvents
Odour threshold:	not applicable
Melting point/freezing point:	-154 °C Source: Hydrocarbons, C6, isoalkanes, <5% n-hexane
Initial boiling point and boiling range:	55 °C Source: Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane
Flammability:	Highly flammable liquid and vapour.
Lower and upper explosion limit:	
Lower explosion limit:	0,8 Vol-% Source: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
Upper explosion limit:	14,3 Vol-% Source: Acetone
Flash point:	-25 °C
Auto-ignition temperature:	> 200 °C Source: Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane
Decomposition temperature:	not applicable
pH at 20 °C:	not relevant

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 6 00021 00000 epple Dilution 477
Print date 09.05.2023 Revision date 09.05.2023
Version 8.0 09.05.2023

EN
Page 7 / 13

Cinematic viscosity (40°C):	0,53 mm²/s
Viscosity at 20 °C:	0,4 mPa* s
Solubility(ies):	
Water solubility at 20 °C:	partially miscible
Partition coefficient: n-octanol/water:	see section 12
Vapour pressure at 20 °C:	240 mbar Source: Acetone
Density and/or relative density:	
Density at 20 °C:	0,76 g/cm³
Relative vapour density:	not applicable
particle characteristics:	not applicable

9.2. **Other information**

SECTION 10: Stability and reactivity

10.1. **Reactivity**

No information available.

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

not applicable

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. **Information on hazard classes as defined in Regulation (EC) No 1272/2008**

*

Acute toxicity

butanone

oral, LD50, Rat: 2193 mg/kg

Method: OECD 403

dermal, LD50, Rabbit: 8050 mg/kg

Method: OECD 402

Ethyl acetate

oral, LD50, Rat: > 2000 mg/kg

dermal, LD50, Rabbit: > 18000 mg/kg

inhalative (vapours), LC50, Rat: > 22,5 mg/L (6 h); Evaluation The substance or mixture has no acute respiratory toxicity

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 2000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: > 20 mg/L (4 h)

Method: OECD 403

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

dermal, LD50, Rat: > 2000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: > 20 mg/L (4 h)

Method: OECD 403

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 6 00021 00000 epple Dilution 477
Print date 09.05.2023 Revision date 09.05.2023
Version 8.0 09.05.2023

EN
Page 8 / 13

Hydrocarbons, C6, isoalkanes, <5% n-hexane
oral, LD50, Rat: > 5000 mg/kg
Method: OECD 401
dermal, LD50, Rat: > 3000 mg/kg
Method: OECD 402
inhalative (vapours), LC50, Rat: > 20 mg/L (4 h)
Method: OECD 403

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
oral, LD50, Rat: > 5840 mg/kg
Method: OECD 401
dermal, LD50, Rat: > 2920 mg/kg
Method: OECD 402
inhalative (vapours), LC50, Rat: 23,3 mg/L (4 h)
Method: OECD 403

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye irritation.

Ethyl acetate

Skin, Rabbit (4 h): Evaluation non-irritant.

eyes, Rabbit: Evaluation mild irritant.

Method: OECD 405

Respiratory or skin sensitisation

Ethyl acetate

Skin, Skin sensitization according to Magnusson/Kligman (maximization test), Guinea pig ; Evaluation not sensitising.

Method: OECD 406

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Ethyl acetate

Reproductive toxicity; Evaluation From the available data there are no indications of reproductive toxicity.

genotoxicity; Evaluation No evidence of a mutagenic effect.

Method: OECD 471 (Ames test)

in-vitro; Salmonella typhimurium; with and without metabolic activation

genotoxicity; Evaluation negative

Method: OECD 473

in-vitro; Chinese hamster ovary cells; with and without metabolic activation

genotoxicity; Evaluation negative

Method: OECD 476

in-vitro; mouse lymphoma cells; with and without metabolic activation

genotoxicity; Evaluation negative

Method: OECD 474

in-vivo; Mouse

STOT-single exposure; STOT-repeated exposure

May cause drowsiness or dizziness.

Aspiration hazard

May be fatal if swallowed and enters airways.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. Toxicity

butanone

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 2993 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 308 mg/L (48 h)

Method: OECD 202

Ethyl acetate

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 230 mg/L (96 h)

Flow test

Daphnia toxicity, EC50, Daphnia cucullata: 165 mg/L (48 h)

aquatic, freshwater

Algae toxicity, ErC50, Desmodesmus subspicatus: > 100 mg/L (72 h)

Method: OECD 201

Bacteria toxicity, NOEC, Pseudomonas putida: 650 mg/L (16 h)

Method: DIN 38412

Fish toxicity, EC50: 220 mg/L (96 h)

Daphnia toxicity, EC50, Artemia salina: 346 mg/L (24 h)

aquatic, marine water

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

Fish toxicity, LL50, Oncorhynchus mykiss (Rainbow trout): 12 mg/L (96 h)

Daphnia toxicity, EL50, Daphnia magna (Big water flea): 3 mg/L (48 h)

Algae toxicity, ErL50, Pseudokirchneriella subcapitata: 55 mg/L (72 h)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Fish toxicity, LL50, Oncorhynchus mykiss (Rainbow trout): 11,4 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EL50, Daphnia magna (Big water flea): 3 mg/L (48 h)

Method: OECD 202

Algae toxicity, EL50, Pseudokirchneriella subcapitata: 30 mg/L (72 h)

Method: OECD 201

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Fish toxicity, LC50, Oryzias latipes (Ricefish): > 1 mg/L (48 h)

Daphnia toxicity, LC50, Daphnia magna (Big water flea): 3,87 mg/L (48 h)

Algae toxicity, ErL50, Pseudokirchneriella subcapitata: 55 mg/L (72 h)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Fish toxicity, LL50, Oncorhynchus mykiss (Rainbow trout): 13,4 mg/L (96 h)

Algae toxicity, EL50, Pseudokirchneriella subcapitata 10 - 30 mg/L (72 h)

Daphnia toxicity, EL50, Daphnia magna: 3 mg/L (48 h)

Long-term Ecotoxicity

Toxic to aquatic life with long lasting effects.

Ethyl acetate

Fish toxicity, NOEC, Pimephales promelas (fathead minnow): < 9,65 mg/L (32 d)

Daphnia toxicity, NOEC, Daphnia magna (Big water flea): 2,4 mg/L (21 d)

Bacteria toxicity, NOEC, Pseudomonas putida: 650 mg/L (16 h)

Method: DIN 38412

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

Algae toxicity, NOELR, Pseudokirchneriella subcapitata: 30 mg/L (72 h)

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Algae toxicity, NOELR, Pseudokirchneriella subcapitata: 30 mg/L (72 h)

Article No.: 6 00021 00000 epple Dilution 477
Print date 09.05.2023 Revision date 09.05.2023
Version 8.0 09.05.2023

EN
Page 10 / 13

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
Daphnia toxicity, NOELR, Daphnia magna: 1 mg/L (21 day(s))
Daphnia toxicity, EL50, Daphnia magna: 1,6 mg/L (21 day(s))
Algae toxicity, NOELR, Pseudokirchneriella subcapitata: 10 mg/L (72 h)

12.2. Persistence and degradability

butanone
oxygen consumption: 98 % (28 d)

Ethyl acetate
Biodegradation, aerobic: 69 % (20 d); Evaluation Readily biodegradable
oxygen consumption: 62 % (5 d)

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane
Biodegradation: 98 % (28 d); Evaluation Readily biodegradable

Hydrocarbons, C6, isoalkanes, <5% n-hexane
Biodegradation: 98 % (28 d); Evaluation Readily biodegradable
Method: OECD 301F

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
Biodegradation: 98 % (28 d)

12.3. Bioaccumulative potential

butanone
Partition coefficient: n-octanol/water: 0,3

Ethyl acetate
Partition coefficient: n-octanol/water: 0,68

Bioconcentration factor (BCF)

Ethyl acetate
Bioconcentration factor (BCF), Leuciscus idus (golden orfe): 30

12.4. Mobility in soil

Ethyl acetate
soil, Adsorption: Evaluation Due to the low n-octanol/water distribution coefficient, adsorption on the ground is not to be expected.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Observe in addition any national regulations!

List of proposed waste codes/waste designations in accordance with EWC

140603* other solvents and solvent mixtures

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package

Dispose of packaging and contaminated filters at a official hazardous waste incinerator facility.

Recommendation:

Waste codes / waste designations according to EWC / AVV: 15 01 10*

Non-contaminated packages may be recycled.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 6 00021 00000 epple Dilution 477
Print date 09.05.2023 Revision date 09.05.2023
Version 8.0 09.05.2023

EN
Page 11 / 13

SECTION 14: Transport information

- 14.1. **UN number or ID number** UN 1993
- 14.2. **UN proper shipping name** *
- Land transport (ADR/RID): Flammable liquid, n.o.s.
(ethyl acetate)
- Sea transport (IMDG): FLAMMABLE LIQUID, N.O.S.
(ethyl acetate, hydrocarbons, C6-C7, isoalkane cyclics, <5% n-hexan)
- Air transport (ICAO-TI / IATA-DGR): Flammable liquid, n.o.s.
(ethyl acetate)
- 14.3. **Transport hazard class(es)** 3
- 14.4. **Packing group** II
- 14.5. **Environmental hazards** *
- Land transport (ADR/RID) DANGEROUS FOR THE ENVIRONMENT
Marine pollutant p / hydrocarbons, C6-C7, isoalkane
- 14.6. **Special precautions for user**
- Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.
Advices on safe handling: see parts 6 - 8
- Further information**
- Land transport (ADR/RID)**
- Tunnel restriction code D/E
special prescription 640D
- Sea transport (IMDG)**
- EmS-No. F-E, S-E
- 14.7. **Maritime transport in bulk according to IMO instruments**
- No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

- 15.1. **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- EU legislation**
- Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]**
VOC-value (in g/L): 754
- National regulations**
- Restrictions of occupation**
Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Further details:

For professional use only. Product is not intended for consumer use.

Substance/product listed in the following inventories:

AICS listed
DSL listed
EHS no information

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 6 00021 00000 epple Dilution 477
 Print date 09.05.2023 Revision date 09.05.2023
 Version 8.0 09.05.2023

EN
 Page 12 / 13

IECSC listed
 KECI listed
 MITI no information
 NZLoC no information
 PICCS listed
 TCSI no information
 TSCA listet

15.2. **Chemical Safety Assessment** *

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
205-500-4 141-78-6	Ethyl acetate	01-2119475103-46
200-662-2 67-64-1	Acetone	01-2119471330-49
926-605-8	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	01-2119486291-36
921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	01-2119475514-35
927-510-4	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	01-2119475515-33
931-254-9	Hydrocarbons, C6, isoalkanes, <5% n-hexane	01-2119484651-34
201-159-0 78-93-3	butanone	01-2119457290-43
203-777-6 110-54-3	n-Hexane	01-2119480412-44
203-806-2 110-82-7	cyclohexane	01-2119463273-41

SECTION 16: Other information *

Full text of classification in section 3

Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging fertility.
STOT RE 2 / H373	STOT-repeated exposure	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic organisms.
Aquatic Chronic 1 / H410	Hazardous to the aquatic environment	Very toxic to aquatic life with long lasting effects.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2	Flammable liquids	On basis of test data.
Skin Irrit. 2	Skin corrosion/irritation	Calculation method.
Eye Irrit. 2	Serious eye damage/eye irritation	Calculation method.
STOT SE 3	STOT-single exposure	Calculation method.
Asp. Tox. 1	Aspiration hazard	Calculation method.
Aquatic Chronic 2	Hazardous to the aquatic environment	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



Article No.: 6 00021 00000 epple Dilution 477
Print date 09.05.2023 Revision date 09.05.2023
Version 8.0 09.05.2023

EN
Page 13 / 13

EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version