

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 6 00021 00000 epple Dilution 477
Print date 14.04.2022 Revision date 12.01.2022
Version 7.2 14.04.2022

EN
Page 1 / 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Article No. (manufacturer/supplier): 6 00021 00000
Trade name/designation epple Dilution 477

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Material for cleaning parts and for the dilution of epple products

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

E. Epple & Co. GmbH

Hertzstr. 8

71083 Herrenberg

Telephone: +49 7032 / 9771-17

Telefax: +49 7032 / 9771-60

www.epple-chemie.de

Department responsible for information:

laboratory

E-mail (competent person)

labor@epple-chemie.de

1.4. Emergency telephone number

Information center against poisoning Bonn

+49 (0) 228 / 19 240 (Advice in German)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2 / H225

Flammable liquids

Highly flammable liquid and vapour.

Skin Irrit. 2 / H315

Skin corrosion/irritation

Causes skin irritation.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

STOT SE 3 / H336

STOT-single exposure

May cause drowsiness or dizziness.

Asp. Tox. 1 / H304

Aspiration hazard

May be fatal if swallowed and enters airways.

Aquatic Chronic 2 / H411

Hazardous to the aquatic environment

Toxic to aquatic life with long lasting effects.

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H225

Highly flammable liquid and vapour.

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

H304

May be fatal if swallowed and enters airways.

H411

Toxic to aquatic life with long lasting effects.

Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261

Avoid breathing vapours.

P280

Wear protective gloves.

P332 + P313

If skin irritation occurs: Get medical advice/attention.

P370 + P378

In case of fire: Use extinguishing powder or sand to extinguish.

P501

Dispose of contents/container in accordance with local/regional/ national/international regulations.

Hazard components for labelling

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Supplemental hazard information

EUH066

Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 6 00021 00000 epple Dilution 477
Print date 14.04.2022 Revision date 12.01.2022
Version 7.2 14.04.2022

EN
Page 2 / 10

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description Solvents/Thinner

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No.	REACH No.	weight-%
CAS No.	Designation	
Index No.	classification: // Remark	
927-510-4	01-2119475515-33 Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Skin Irrit. 2 H315 / STOT SE 3 H336 / Asp. Tox. 1 H304 / Aquatic Chronic 2 H411 / Flam. Liq. 2 H225	49,9 - 74,9
205-500-4	01-2119475103-46	
141-78-6	Ethyl acetate	19,9 - 24,9
607-022-00-5	Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	
200-662-2	01-2119471330-49	
67-64-1	Acetone	19,9 - 24,9
606-001-00-8	Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	
201-159-0	01-2119457290-43	
78-93-3	butanone	2,4 - 9,9
606-002-00-3	Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 6 00021 00000 epple Dilution 477
Print date 14.04.2022 Revision date 12.01.2022
Version 7.2 14.04.2022

EN
Page 3 / 10

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetRSIVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Floors must be electrically conductive.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

Ethyl acetate

Index No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

TWA: 730 mg/m³; 200 ppm

STEL: 1460 mg/m³; 400 ppm

Acetone

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 6 00021 00000 epple Dilution 477
Print date 14.04.2022 Revision date 12.01.2022
Version 7.2 14.04.2022

EN
Page 4 / 10

Index No. 606-001-00-8 / EC No. 200-662-2 / CAS No. 67-64-1

TWA: 1810 mg/m³; 750 ppm

STEL: 3620 mg/m³; 1500 ppm

butanone

Index No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

TWA: 600 mg/m³; 200 ppm

STEL: 899 mg/m³; 300 ppm

Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

butanone

Index No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

DNEL long-term dermal (systemic), Workers: 1161 mg/kg

DNEL long-term inhalative (systemic), Workers: 600 mg/m³

DNEL long-term oral (repeated), Consumer: 31 mg/kg

DNEL acute dermal, short-term (local), Consumer: 412 mg/kg

DNEL long-term inhalative (systemic), Consumer: 106 mg/m³

Ethyl acetate

Index No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

DNEL short-term oral (acute), Workers:

DNEL long-term dermal (systemic), Workers: 63 mg/kg bw/day

DNEL acute inhalative (local), Workers: 1468 mg/m³

DNEL acute inhalative (systemic), Workers: 1468 mg/m³

DNEL long-term inhalative (local), Workers: 734 mg/m³

DNEL long-term inhalative (systemic), Workers: 734 mg/m³

DNEL short-term oral (acute), Consumer:

DNEL long-term dermal (systemic), Consumer: 37 mg/kg bw/day

Acetone

Index No. 606-001-00-8 / EC No. 200-662-2 / CAS No. 67-64-1

DNEL long-term dermal (systemic), Workers: 186 mg/kg bw/day

DNEL acute inhalative (local), Workers: 2420 mg/m³

DNEL long-term inhalative (systemic), Workers: 1210 mg/m³

PNEC:

butanone

Index No. 606-002-00-3 / EC No. 201-159-0 / CAS No. 78-93-3

PNEC aquatic, freshwater: 55,8 mg/L

PNEC aquatic, marine water: 55,8 mg/L

PNEC sediment, freshwater: 284,7 mg/kg

PNEC sediment, marine water: 284,7 mg/kg

PNEC, soil: 22,5 mg/kg

Ethyl acetate

Index No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

PNEC aquatic, freshwater: 0,26 mg/L

PNEC aquatic, marine water: 0,026 mg/L

PNEC aquatic, intermittent release: 1,65 mg/L

PNEC sediment, freshwater: 1,25 mg/kg

PNEC sediment, marine water: 0,125 mg/kg

PNEC, soil: 0,24 mg/kg

PNEC sewage treatment plant (STP): 650 mg/L

Acetone

Index No. 606-001-00-8 / EC No. 200-662-2 / CAS No. 67-64-1

PNEC aquatic, freshwater: 10,6 mg/L

PNEC aquatic, marine water: 1,06 mg/L

PNEC aquatic, intermittent release: 21 mg/L

PNEC sediment, freshwater: 30,4 mg/kg

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 6 00021 00000 epple Dilution 477
Print date 14.04.2022 Revision date 12.01.2022
Version 7.2 14.04.2022

EN
Page 5 / 10

PNEC sediment, marine water: 3,04 mg/kg
PNEC, soil: 29,5 mg/kg

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number. Recommendation: Half-face mask Filter type: ABEK-P2

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Appearance:

Liquid

Colour:

translucent

Odour:

like Solvents

Odour threshold:

not applicable

pH at 20 °C:

not relevant

Melting point/freezing point:

-94 °C

Source: Acetone

Initial boiling point and boiling range:

56 °C

Source: Acetone

Flash point:

-25 °C

Evaporation rate:

5,4 mg/s

Source: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

flammability

Burning time:

not applicable

Upper/lower flammability or explosive limits:

Lower explosion limit:

1 Vol-%

Source: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Upper explosion limit:

14,3 Vol-%

Source: Acetone

Vapour pressure at 20 °C:

240 mbar

Source: Acetone

Vapour density:

not applicable

Relative density:

Density at 20 °C:

0,76 g/cm³

Solubility(ies):	
Water solubility at 20 °C:	partially miscible
Partition coefficient: n-octanol/water:	see section 12
Auto-ignition temperature:	246 °C Source: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
Decomposition temperature:	not applicable
Viscosity at 20 °C:	0,4 mPa*s
Explosive properties:	not applicable
Oxidising properties:	not applicable

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

11.1. Information on toxicological effects

Acute toxicity

butanone

oral, LD50, Rat: 2193 mg/kg

Method: OECD 403

dermal, LD50, Rabbit: 8050 mg/kg

Method: OECD 402

Ethyl acetate

oral, LD50, Rat: > 2000 mg/kg

dermal, LD50, Rabbit: > 18000 mg/kg

inhalative (vapours), LC50, Rat: > 22,5 mg/L (6 h)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

oral, LD50, Rat: > 5840 mg/kg

Method: OECD 401

dermal, LD50, Rat: > 2920 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: 23,3 mg/L (4 h)

Method: OECD 403

Skin corrosion/irritation; Serious eye damage/eye irritation

Causes skin irritation.

Causes serious eye irritation.

Ethyl acetate

eyes, Rabbit: Evaluation mild irritant.

Method: OECD 405

Skin, Rabbit (4 h): Evaluation non-irritant.

Article No.: 6 00021 00000 epple Dilution 477
Print date 14.04.2022 Revision date 12.01.2022
Version 7.2 14.04.2022

EN
Page 7 / 10

Respiratory or skin sensitisation

Ethyl acetate

Skin, Guinea pig: ; Evaluation not sensitising.

Method: OECD 406

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

May cause drowsiness or dizziness.

Aspiration hazard

May be fatal if swallowed and enters airways.

Practical experience/human evidence

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. Toxicity

butanone

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 2993 mg/L (96 h)

Method: OECD 203

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 308 mg/L (48 h)

Method: OECD 202

Ethyl acetate

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 230 mg/L (96 h)

Bacteria toxicity, NOEC, Pseudomonas putida: 650 mg/L (16 h)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Fish toxicity, LL50, Oncorhynchus mykiss (Rainbow trout): 13,4 mg/L (96 h)

Algae toxicity, EL50, Pseudokirchneriella subcapitata 10 - 30 mg/L (72 h)

Daphnia toxicity, EL50, Daphnia magna: 3 mg/L (48 h)

Daphnia toxicity, NOELR, Pseudokirchneriella subcapitata: 10 mg/L (72 h)

Long-term Ecotoxicity

Toxic to aquatic life with long lasting effects.

Ethyl acetate

Fish toxicity, NOEC, Pimephales promelas (fathead minnow): < 9,65 mg/L (32 d)

Daphnia toxicity, NOEC, Daphnia magna: 2,4 mg/L (21 d)

Bacteria toxicity, NOEC, Pseudomonas putida: 650 mg/L (16 h)

Method: DIN 38412

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Daphnia toxicity, NOELR, Daphnia magna: 1 mg/L (21 day(s))

Daphnia toxicity, EL50, Daphnia magna: 1,6 mg/L (21 day(s))

12.2. Persistence and degradability

Ethyl acetate

Biodegradation, aerobic: 69 % (20 d); Evaluation Readily biodegradable

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Biodegradation: 81 % (28 d)

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Ethyl acetate

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 6 00021 00000 epple Dilution 477
Print date 14.04.2022 Revision date 12.01.2022
Version 7.2 14.04.2022

EN
Page 8 / 10

Bioconcentration factor (BCF), *Leuciscus idus* (golden orfe): 30

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

140603* other solvents and solvent mixtures

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package

Dispose of packaging and contaminated filters at a official hazardous waste incinerator facility.

Recommendation:

Waste codes / waste designations according to EWC / AVV: 15 01 10*

SECTION 14: Transport information

14.1. UN number

UN 1993

14.2. UN proper shipping name

Land transport (ADR/RID):

Flammable liquid, n.o.s.
(Heptane)

Sea transport (IMDG):

FLAMMABLE LIQUID, N.O.S.
(Heptane)

Air transport (ICAO-TI / IATA-DGR):

Flammable liquid, n.o.s.
(Heptane)

14.3. Transport hazard class(es)

3

14.4. Packing group

II

14.5. Environmental hazards

Land transport (ADR/RID)

DANGEROUS FOR THE ENVIRONMENT

Marine pollutant

p / Heptane

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code

D/E
special prescription 640D

Sea transport (IMDG)

EmS-No.

F-E, S-E

Air transport (ICAO-TI / IATA-DGR)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 6 00021 00000 epple Dilution 477
Print date 14.04.2022 Revision date 12.01.2022
Version 7.2 14.04.2022

EN
Page 9 / 10

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 770

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Substance/product listed in the following inventories:

AICS listed
DSL listed
IECSC listed
KECI listed
MITI listed
PICCS listed
TSCA listet

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
927-510-4	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	01-2119475515-33
205-500-4 141-78-6	Ethyl acetate	01-2119475103-46
200-662-2 67-64-1	Acetone	01-2119471330-49
201-159-0 78-93-3	butanone	01-2119457290-43

SECTION 16: Other information

Full text of classification in section 3

Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2	Flammable liquids	On basis of test data.
Skin Irrit. 2	Skin corrosion/irritation	Calculation method.
Eye Irrit. 2	Serious eye damage/eye irritation	Calculation method.
STOT SE 3	STOT-single exposure	Calculation method.
Asp. Tox. 1	Aspiration hazard	Calculation method.
Aquatic Chronic 2	Hazardous to the aquatic environment	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 6 00021 00000 epple Dilution 477
Print date 14.04.2022 Revision date 12.01.2022
Version 7.2 14.04.2022

EN
Page 10 / 10

EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.